


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 32 Township Number T 11 S Range Number R 16 E

Distance and direction from nearest town or city street address of well if located within city? AT & SF Railway 5th Holiday (Quincy) Topeka Ks

2 WATER WELL OWNER: Atchison, Topeka & Santa Fe Railway RR#, St. Address, Box #: 5th Holiday City, State, ZIP Code: Topeka Ks Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 21.0 ft. ELEVATION: 925.51

Depth(s) Groundwater Encountered 1. 12.35 ft. 2. - ft. 3. - ft.

WELL'S STATIC WATER LEVEL 12.35 ft. below land surface measured on mo/day/yr 9-21-93

Pump test data: Well water was - ft. after - hours pumping - gpm

Est. Yield - gpm; Well water was - ft. after - hours pumping - gpm

Bore Hole Diameter 6 in. to 21.0 ft., and - in. to - ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded X

Blank casing diameter 2 in. to 12.0 ft., Dia - in. to - ft., Dia - in. to - ft.

Casing height above land surface 0.0 in., weight Sch 40 lbs./ft. Wall thickness or gauge No. -

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 12.0 ft. to 21.0 ft., From - ft. to - ft., From - ft. to - ft.

GRAVEL PACK INTERVALS: From 6.0 ft. to 21.0 ft., From - ft. to - ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0.0 ft. to 6.0 ft., From - ft. to - ft., From - ft. to - ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.7	Concrete			
0.7	1.2	Gravel (coarse)			
1.2	2.0	Silty clay Gr Br			
2.0	3.0	Limestone (Buff)			
3.0	7.0	Shale Tan to Brown			
7.0	15.9	Limestone Buff to tan			
15.9	16.2	Limestone Buff to tan			
16.2	21.0	Sandstone dk Gr			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1-10-94 under the business name of Terracon Consultants Inc by (signature) Richard D. Murphy