


1 LOCATION OF WATER WELL: County: Shawnee Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 36 Township Number T 11 Range Number R 16

Distance and direction from nearest town or city street address of well if located within city? 6000 S.E. 2nd Street, Telumseh, Kansas

2 WATER WELL OWNER: Flexel, Inc. RR#, St. Address, Box #: 6000 S.E. 2nd Street City, State, ZIP Code: Telumseh, Kansas Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 26.0 ft. ELEVATION: 13.3 ft. WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 40.8 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 2 in. to 15.9 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 2.1 in., weight Sch. 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 15.9 ft. to 24.9 ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 12.9 ft. to 26.0 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0.0 ft. to ft. From 12.9 ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Plastic Plant

Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0.0-1.5 Lean Clay Gray Brown, 1.5-3.2 Med Sand Brown, 3.2-5.1 Med Sand Brown with Silt Layers Gray Brown, 5.1-7.8 Fine Sand Brown, 7.8-12.0 Med - Coarse Sand Brown, 12.0-14.9 Fine Sand Gray, 14.9-39.5 Med - Coarse Sand and Gravel Gray, 39.5-39.9 Shale Gray Olive Green, 39.9-40.8 Shale Gray

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) December 18, 1991 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1/9/92 under the business name of Terracon Consultants SE, Inc. by (signature) Ronald G. Smith