


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SW 1/4 Section Number 31 Township Number T 11 S Range Number R 16 EN
 County: Shawnee
 Distance and direction from nearest town or city street address of well if located within city?
801 SW Topeka Ave., Topeka, KS.

2 WATER WELL OWNER: Kwik Shop
 RR#, St. Address, Box #: 734 E. 4th Ave, Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hutchinson, KS. 67504-1927 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 18'6" ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered: 9'5" ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 6.95 ft. below land surface measured on mo/day/yr 5-18-95
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm; Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 3 1/2" to 4" ft., and in. to ft.
 WELL WATER TO BE USED FOR: 5 1/2" to 18'6" Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes..... No. X.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded. X
 Blank casing diameter 2.375 in. to 8' ft. Dia in. to ft. Dia in. to SDR 13 ft.
 Casing height above land surface Flush Hk. Ø in., weight lbs./ft. Wall thickness or gauge No. SCH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 18' ft. to 8' ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 18'6" ft. to 6' ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 6' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? Southeast How many feet? 25'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Grass-dk brn silty clay, root earthy odor.	frag.		
2	7.50	Med. brn clay, firm, tight, iron oxides, no odor w/ small ls. rx. gravel.			
7.50	10.50	Green-dk gray mottled clay w/ ls. rx. gravel, moist to wet at 9 1/2'. Mod odor, iron oxides, sm. ls. rx. layer at 9 1/2'.			
10.50	12	Yellow mustard colored weathered shale, dry, tight, faint odor.			
12	15	Limestone, gray-tan, interbedded, hard.			
15	18'6"	Gray shale, dry, no odor.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-24-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539. This Water Well Record was completed on (mo/day/yr) 5-18-95 under the business name of JB Environmental Drilling by (signature) James Becker

OFFICE USE ONLY
T
R
EM
SEC