4 LOCATION O	VALATED VALEL I		VVELL RECOR	D FORM VVV			lumba-	Danas N	humbor
	nee yersor	Fraction SW 1/4	SW 1/4	SW 1/4	Section Number 18	Township N	umber S	Range N R <b>17</b>	EW
	ection/from nearest tov							., 1/	<u>J.</u>
	East & Deltor Rd.			locatoa viidiii i	only i				
	L OWNER: Quality	· · · · · · · · · · · · · · · · · · ·							
_		-				Daniel of Ami		: £ \ A / t	D
•	, Box# : 1900 No	-				Board of Agric		ion of vvater	Resources
City, State, ZIP		Kansas 66608		. 26		Application No		70.10	
3 LOCATE WE	NICECTION DOV: L	4 DEPTH OF CO							
_	N	Depth(s) Groundw							
<b>†</b>		WELL'S STATIC \							
		Pump t	est data: Well	water was	N.Aft.a	fter	. hours pum	nping	gpm
INV		Est. Yield NA	gpm: Well	water was	ft. a	ifter	. hours pun	nping	gpm
W <u> </u>		Bore Hole Diamet	er <b>§</b> i	n. to	<b>26</b> ft.,	and	in.	to	ft.
₹ w <b> </b> †	<del>                                     </del>	WELL WATER TO	BE USED AS:	5 Public w	ater supply	8 Air conditioni	ng <u>11</u> l	njection well	
. ! :		1 Domestic	3 Feedlot	6 Oil field v	vater supply	9 Dewatering	(12)	Other (Specify	/ below)
sv	SE	2 Irrigation	4 Industrial	7 Lawn an	d garden only	10 Monitoring we		Soil Vapor	Extract.
↓  x i		Was a chèmical/b	oacteriological s						
<u> </u>	1 , 1	submitted	_	•		ater Well Disinfec		No	-/
TYPE OF BL	NK CASING USED:	F	Wrought iron	8 Cc	ncrete tile	CASING JO	INTS: Glued	Clan	nped
1 Steel	3 RMP (SR		Asbestos-Cen		ner (specify belo			ed	•
2PVC	4 ABS	,	' Fiberglass			-		ded. 🗸	
	neter		•						
_	ove land surface					ft. Wall thickness			
	N OR PERFORATION		i., weight		PVC		bestos-ceme		•. • • • • • • • • • • • • • • • • • •
			- Fibouriosa						
1 Steel	3 Stainless		Fiberglass		RMP (SR)				
2 Brass	4 Galvanize		Concrete tile	_	ABS		ne used (ope	•	
	REPORATION OPENING			Sauzed wrappe		8 Saw cut		11 None (or	en hole)
1 Continu				Vire wrapped		9 Drilled holes			
2 Louvere		ey punched		orch cut		10 Other (specif	• •		
SCREEN-PERF	RATED INTERVALS:				•	om			
	D. A. O. C. II. EE ED. (A) O.					om			
GRAVE	. PACK INTERVALS:					om			
						om	π.	to	π.
GROUT MAT			Cement grout			Other			
Grout Intervals:	From	ft. to 13	ft., From .	13	ft. to 15 .	ft., From .	· · · · · · · · · · ·	. ft. to	ft.
What is the near	est source of possible	contamination:				stock pens		oandoned wat	
<ol> <li>Septic tanl</li> </ol>	4 Latera	al lines	7 Pit priv	y		storage		l well/Gas wel	
2 Sewer lines 5 Cess pool			8 Sewage lagoon 12 Fe			ertilizer storage 16 Other (specify below)			oelow)
3 Watertight	sewer lines 6 Seepa	age pit	9 Feedya	ard	13 Inse	cticide storage			
Direction from w	ll? W					ny feet? 60			
FROM T		LITHOLOGIC LO	OG	FROM	1 TO	P	_UGGING IN	TERVALS	
0 0.									
0.5 4	Clay, Very Da								
4 1	Clay, Medium								,
11 10	Silt, Light Bro	own							
16 22	Silt, Medium 1	Brown							
22 20	Clay, Medium	Brown							
				-					
						VE5 Teg# 0014	5323 Flucks	nount	
				SVE5 , Tag # 00145323 , Flushmount  Project Name: Quality Gas					
						GeoCore # 250 , K	_•	A 1275	
	S OR LANDOWNER:								
	ed on (mo/day/year) .					ecord is true to th	•		
Kansas Water V	ell Contractor's Licens	se No	527	. This Water V	Vell Record was	completed on (m	o/day/yr)	6/18/9	96
under the busine	s name of	GeoCore	Services, In	с	by (signa	iture)	Hale o	a Koled	
	Use typewriter or ball poin	nt pen. <u>PLEASE PRE</u>	SS FIRMLY and PR	RINT clearly. Pleas	e fill in blanks, unde	or circle the corre	ect answers. Se	end top three cop	ies to Kansas