


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 18 Township Number T 11 S Range Number R 17 EW
 County: JEFFERSON
 Distance and direction from nearest town or city street address of well if located within city?
1/4 M N. 1/2 M W of GRANTVILLE, APPROX 150 N of HWY 24 **PW-A**

2 WATER WELL OWNER: QUALITY GAS SHOP
 RR#, St. Address, Box #: 1900 N. TOPEKA AVE Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: TOPEKA, KS 66608 Application Number: 4/A

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 45.0' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 28.0' ft. 2. - ft. 3. - ft.
 WELL'S STATIC WATER LEVEL: 28.32 ft. below land surface measured on mo/day/yr 5/7/94
 Pump test data: Well water was - ft. after - hours pumping - gpm
 Est. Yield - gpm Well water was - ft. after - hours pumping - gpm
 Bore Hole Diameter 1.75 in. to 45.5 ft., and - in. to - ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes - No X If yes, mo/day/yr sample was submitted -
 Water Well Disinfected? Yes - No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded -
 7 Fiberglass Threaded X
 Blank casing diameter 20 4" in. to 25 ft. Dia - in. to - ft. Dia - in. to - ft.
 Casing height above land surface 1.5 in. weight - lbs./ft. Wall thickness or gauge No. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) -
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) -
 SCREEN-PERFORATED INTERVALS: From 45 ft. to 25 ft. From - ft. to - ft. From - ft. to - ft.
SAND GRAVEL PACK INTERVALS: From 45 ft. to 23 ft. From - ft. to - ft. From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -
 Grout Intervals: From 23 ft. to SURFACE ft. From - ft. to - ft. From - ft. to - ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage CONTAMINATED SITE
 Direction from well? - How many feet? 250 EAST

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>0.8</u>	<u>ASPHALT</u>			
<u>0.8</u>	<u>12.0</u>	<u>GREY-BROWN SILTYCLAY, FIRM</u>			
<u>12.0</u>	<u>25.0</u>	<u>BROWN SILTYCLAY, FIRM</u>			
<u>25.0</u>	<u>30.0</u>	<u>SAND, STIFF</u>			
<u>30.0</u>	<u>45.0</u>	<u>MED-COARSE GRAIN SAND</u>			
		<u>T.D. 45.5'</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/6/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 05-24-94 under the business name of EBBERTS DRILLING by (signature) Angela Ebberts

00000