

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215 *ccc*

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

dda 23

1. Location of well:	County JEFFERSON	Fraction <i>SW SW SW</i> NE 1/4 SE 1/4 SE 1/4	Section number 25	Township number T 11 S R 17 E	Range number 17
2. Distance and direction from nearest town or city:	3. Owner of well:				
Street address of well location if in city:	City, state, zip code:				
4. Locate with "X" in section below:			Sketch map:		
5. Type and color of material			6. Bore hole dia. <u>8</u> in. Completion date <u>6-9-76</u> Well depth <u>50</u> ft.		
			7. <input checked="" type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
			8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
			9. Casing: Material <u>STP</u> Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>18</u> in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight <u>18</u> lbs./ft. Dia. <u>5</u> in. to <u>50</u> ft. depth Wall Thickness: inches or Dia. <u>5</u> in. to <u>50</u> ft. depth gage No. <u>200</u>		
			10. Screen: Manufacturer's name <u>SUN FLOWER</u> Type <u>STP</u> Dia. <u>5"</u> Slot/gauze <u>1/8" x 2"</u> Length <u>5'</u> Set between <u>45</u> ft. and <u>50</u> ft. ft. and <u>50</u> ft. Gravel pack <input checked="" type="checkbox"/> Size range of material <u>1/4" - 1/2"</u>		
			11. Static water level: <u>6-9-76</u> mo./day/yr. <u>27</u> ft. below land surface Date <u>6-9-76</u>		
			12. Pumping level below land surfaces: <u>27</u> ft. after <u>1</u> hrs. pumping <u>16.5</u> g.p.m. <u>27</u> ft. after <u>12</u> hrs. pumping <u>16.5</u> g.p.m. Estimated maximum yield <u>40</u> g.p.m.		
			13. Water sample submitted: <u>6-9-76</u> mo./day/yr. Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Date <u>6-9-76</u>		
			14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter <u> </u> Inches above grade		
			15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From <u>4</u> ft. to <u>14</u> ft.		
			16. Nearest source of possible contamination: ft. <u>60</u> Direction <u>SW</u> Type <u>C.T.</u> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
			17. Pump: Manufacturer's name <u>QUALDS</u> Not installed Model number <u>103</u> HP <u>1/2</u> Volts <u>115</u> Length of drop pipe <u>44</u> ft. capacity <u>26</u> g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input checked="" type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
(Use a second sheet if needed)					
18. Elevation: <u>66?</u>	19. Remarks: OWNER AGREES TO POOR SLAB 4'X4'				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. H. L. PETTIT Business name <u> </u> License No. <u> </u> Address <u>905 N. MICHIGAN 333</u> Signed <u>H. L. Pettit</u> Date <u>6-9-76</u> Authorized representative
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	<i>David M. Lines</i>				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

BR < 811²

7 = 835

T 11 S R 17 E
 22 NE SE SE
 1/4 1/4 1/4
 Sec