


1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 NE 1/4 Section Number 25 Township Number T 11 S Range Number R 18 EW
 County: JEFFERSON

Distance and direction from nearest town or city street address of well if located within city?

2 mi EAST OF PERRY, KS.

2 WATER WELL OWNER: JEFFERSON CO. RWD No. 2 WELL No. 3
 RR#, St. Address, Box #: C/O JAMES I. BIGGS
 City, State, ZIP Code: RT. 1, PERRY KANSAS 66073
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 64 ft. ELEVATION: 786
 Depth(s) Groundwater Encountered 1. 17 ft. 2. — ft. 3. — ft.
 WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr MAY 17, 1985
 Pump test data: Well water was 19 ft. after 3 hours pumping 60.4 gpm
 Est. Yield — gpm Well water was — ft. after — hours pumping — gpm
 Bore Hole Diameter 18 in. to 64 ft., and — in. to — ft.
 WELL WATER TO BE USED AS: Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Welded Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Threaded
 Blank casing diameter 12 in. to 46 ft., Dia — in. to — ft., Dia — in. to — ft.
 Casing height above land surface 24 in., weight 43.77 lbs./ft. Wall thickness or gauge No. 330"
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 44 ft. to 64 ft., From — ft. to — ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 64 ft., From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From — ft. to — ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage NONE KNOWN

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4'0"	BROWN CLAY			
4'0"	18'0"	GRAY-BROWN CLAY			
18'0"	25'0"	BROWN FINE TO MED. SAND			
25'0"	40'0"	BROWN MED TO CRSE W/TK FINE SAND			
40'0"	55'0"	BROWN MED TO CRSE W/ SOME FINE SAND			
55'0"	64'0"	BROWN CRSE TO MED W/TK FINE SAND			
		GRAVEL AND BLDGS			
		TOTAL DEPTH			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) JANUARY 29, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) JUNE 21, 1985 under the business name of LAYNE WESTERN Co., INC. by (signature) Stephen P. Daily

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.