

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Jefferson	SW 1/4 SW 1/4 SW 1/4	23	T 11 S	R 18 E

Distance and direction from nearest town or city street address of well if located within city?

Front Street, Perry, Kansas

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code :	

**City of Perry
Perry, Kansas 66066**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 848.63
	Depth(s) Groundwater Encountered 1. 24 ft. 2. — ft. 3. — ft.
	WELL'S STATIC WATER LEVEL 22.72 ft. below land surface measured on mo/day/yr 1-26-95
	Pump test data: Well water was — ft. after — hours pumping — gpm
	Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm
	Bore Hole Diameter 8.625 in. to 30 ft. and — in. to — ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well m.w.-3	
Was a chemical/bacteriological sample submitted to Department? Yes — No X If yes, mo/day/yr sample was submitted —	
Water Well Disinfected? Yes — No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded —
Blank casing diameter 2 in. to 19.5 ft. Dia — in. to — ft. Dia — in. to — ft.			Threaded X
Casing height above land surface 0 in. weight sch 40 PVC lbs./ft. Wall thickness or gauge No. —			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 19.5 ft. to 29.5 ft.	From — ft. to — ft.	From — ft. to — ft.
SAND	From 18.5 ft. to 30 ft.	From — ft. to — ft.	From — ft. to — ft.
GRAVEL	From — ft. to — ft.	From — ft. to — ft.	From — ft. to — ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From GL ft. to 16.5 ft. From 16.5 ft. to 18.5 ft. From — ft. to — ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? —				
How many feet? —				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1.0	Fill			
1.0	8.0	Silty Clay			
8.0	15.0	Clayey Silt			
15.0	19.0	Silty Clay			
19.0	24.0	Clayey Silt			
24.0	25.0	Silty Sand			
25.0	30.0	Sand			
30.0	TD	End of Borehole			

Flush Mount Waiver
Don Taylor
1/12/95

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-25-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 2-21-95 under the business name of AET-Associated Environmental, Inc. (signature) <i>Don Taylor</i>
