

1 LOCATION OF WATER WELL: County: JEFFERSON	Fraction NE 1/4 NE 1/4 SE 1/4	Section Number 23	Township Number T 11 S	Range Number R 18 E/W
--	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

5/8 E. of Perry

2 WATER WELL OWNER: Randy Harries	#2 Heat pump hole	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 211 E. Bridge St.	North hole	Application Number:
City, State, ZIP Code: Perry, KS 66073		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 200' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 0 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6" in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) HEAT PUMP Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height 36 in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) NA
SCREEN-PERFORATED INTERVALS: From NA ft. to NA ft., From ft. to ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 5 ft. to 30 ft., From ft. to ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? west			How many feet? 150'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay-Brown 74-105	Shale-Gr	192-200	Shale-Grey
3	7	Shale-Yellow 105-112	Limestone-Grey		
7	10	Limestone-Yellow 112-115	Shale-Grey		
10	14	Shale-Yellow 115-124	Limestone-Yellow		
14	17	Limestone-Yellow 124-133	Limestone-Gr		
17	18	Shale-Yellow 133-138	Shale-Grey		
18	22	Limestone-Grey 138-141	Limestone-Gr	Benseal 30-200'	
22	26	Shale-Grey 141-152	Shale-Grey		
26	29	Limestone-Grey 152-163	Limestone-Grey		
29	33	Shale-Grey 163-184	Shale-Grey		
33	43	Sandstone-Y 184-185	Limestone-Grey		
43	61	Shale-Grey 185-187	Shale-Grey		
61	64	Limestone-Grey 187-189	Shale-Red		
64	72	Shale-Grey 189-190	Limestone-Grey		
72	74	Limestone-Grey 190-192	Shale-Red		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-15-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 5-25-95 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Strader
---