

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: JEFFERSON		SW 1/4 SW 1/4 NE 1/4		20		T 11 S		R 19 EW			
Distance and direction from nearest town or city street address of well if located within city? 1 mile north, 1/4 east of Williamstown											
2 WATER WELL OWNER: Mick Jamison											
RR#, St. Address, Box # : Rt. 1 Box 291						Board of Agriculture, Division of Water Resources					
City, State, ZIP Code : Perry, KS 66044						Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION:								
1 Mile			Depth(s) Groundwater Encountered 1. 15-30' ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL 15' ft. below land surface measured on mo/day/yr 8-04-89								
			Pump test data: Well water was ft. after hours pumping gpm								
			Est. Yield .25 gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter 8 3/4 in. to ft., and in. to ft.								
WELL WATER TO BE USED AS:			5 Public water supply 8 Air conditioning 11 Injection well								
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes X No											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped											
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded											
7 Fiberglass Threaded											
Blank casing diameter 5" in. to 0-15 ft., Dia 5" in. to 35-60 ft., Dia in. to ft.											
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 15 ft. to 35 ft., From ft. to ft.											
From ft. to ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 14 ft. to 58 ft., From ft. to ft.											
From ft. to ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug											
Grout Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage											
Direction from well? north How many feet? 800'											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		24		Clay-Brown							
24		27		FS-CS-Med-Pea Gravel, cherty							
27		37		Clay-Brown							
37		41		Shale-Yellow						8-08-89 Permission to grout	
41		58		Shale-Grey						0-14' by Don Taylor	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-04-89 and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 10-9-89											
under the business name of STRADER DRILLING CO., INC. by (signature) <i>Don Taylor</i>											