

1 LOCATION OF WATER WELL: County: Jefferson		Fraction NE 1/4 NW 1/4 NW 1/4		Section Number 35		Township Number T 11 S		Range Number R 19 EW	
Distance and direction from nearest town or city street address of well if located within city? Jefferson - Douglas County Landfill, Perry, Kansas									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Hamm, N.R. Asphalt, Inc. P.O. Box 17 Perry, Kansas 66073 Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 51.8 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 in. to 6.6 ft. and 5 in. to 51.8 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 41.75 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 24 in., weight Sch. 40 PVC lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 41.75 ft. to 50.7 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 39.0 ft. to 51.8 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 37.0 ft. From 37.0 ft. to 39.0 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? away Landfill some distance away									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 2" Topsoil									
2" 6.6" Lean Clay, Brown									
6.6 20.0 Weathered Limestone									
20.0 22.7 Weathered Shale, Gray									
22.7 26.5 Shale, Dark Gray and Black									
26.5 28.5 Limestone, Gray									
28.5 42.0 Shale, Gray, Trace Limestone Stringer									
42.0 49.8 Weathered Limestone									
49.8 51.8 Limey Shale, Olive Gray									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/18/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11/1/91 under the business name of Terracon Consultants, SE by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									