			WAT	ER WELL RECORD	Form WWC-5	KSA 82	a-1212 1	4918001	MW-11
LOCATIO	ON OF WAT Jeffer	ER WELL:	Fraction			tion Number	1 11		Range Number
Journey.			NE 1			35	T 11	S	R 19 (E)W
Distance an	d direction	from nearest tov Jefferson	vn or city street - Douglas	address of well if locat County Landfi	ed within city? 11, Perry	, Kansas	5		
WATER	WELL OW	NER:	Hamm, N	.R. Asphalt,	inc.				
RR#, St. A	ddress, Box	# :	P.O. Bo				Board o	of Agriculture,	Division of Water Resources
City, State,	ZIP Code	:	Perry.	Kansas 66073			Applica	tion Number:	
LOCATE	WELL'S LO	CATION WITH	4 DEPTH OF	COMPLETED WELL.	428	. ft. ELEVA	ATION:		
AN "X" I	N SECTION	I BOX:							3
- W	- NW	NE IX	WELL'S STATION  Pun  Est. Yield  Bore Hole Dian	C WATER LEVEL	ter was	elow land su ft. a .5 ft. a	rface measured after	on mo/day/yr hours pu hours pu in	Imping gpm Imping 42.8 gpm . to
-	-			TO BE USED AS:	5 Public wate	r suppiy	8 Air condition	ing 11	injection well
	_ sw	SE	1 Domestic		6 Oil field wat	er supply	9 Dewatering	12	Other (Specify below)
	1	1	2 Irrigation						
L	T <sup>*</sup>	1	Was a chemica	l/bacteriological sample	submitted to De				, mo/day/yr sample was sub
·			mitted				ater Well Disinfe		
TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 Concre				d Clamped
1 Stee		3 RMP (S	R)	6 Asbestos-Cement					led
<b>②</b> PV0		4 ABS		7 Fiberglass					aded
Blank casin	g diameter	2	.in. to 29 .	7 ft., Dia	in. to		ft., Dia		in. to ft.
Casing heig	ht above la	nd surface	. 30	in., weight . <b>S.ch</b> . 8	10 .PVC . <u>.</u>	lbs.	/ft. Wall thickne	ss or gauge N	lo
YPE OF S	SCREEN OF	R PERFORATIO	N MATERIAL:		<b>Ø</b> PV	С		Asbestos-ceme	
Stee	el	3 Stainles		5 Fiberglass	8 RM	P (SR)	11 (	Other (specify)	
2 Bra	ss	4 Galvaniz	zed steel	6 Concrete tile	9 AB			None used (or	•
CREEN O	R PERFOR	RATION OPENIN	IGS ARE:		zed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Lou	vered shutte	er 4 K	ey punched		h cut				
		ED INTERVALS: CK INTERVALS:	From	ft. to ft. to	42.8	ft., Fro	om	ft. 1	to
CROUT	MATERIAL	. Allocat	cement		A Banta	nito 1			,
GROUT Grout Interv	MATERIAL als: Fron	n 0	.ft. to	5 ft., From	255 ft.	to 27.			ft. to
What is the	nearest so	urce of possible	contamination:			10 Live:	stock pens	14 A	bandoned water well
		4 Later		7 Pit privy		11 Fuel	storage	15 C	Dil well/Gas well
2 Sewer lines 5 Cess				8 Sewage la					Other (specify below)
3 Watertight sewer lines 6 Seep			•	9 Feedyard	_	13 Insecticide storage			l some distance
Direction fro	•	•	<b>5</b> ,	·		How ma	any feet?		away
FROM	то		LITHOLOGIC	LOG	FROM	ТО		PLUGGING I	NTERVALS
0	2"	Topsoil							
2"	1.5			d Limeston, Br	own				
1.5	12.5	Weather	ed Limesto	ne					
12.5	14.8	Weather	ed Clavey	Shale, Tan Gra	y Brown				
4.8	17.7		ed Shale,						
17.7	18.8		ne, Gray						
18.8	19.5			Shale, Tan Gra	y Brown				
19.5	31.0		Shale, Gra						
31.0	31.8	Weather	ed Clavev	Shale, Gray Bi	rown				
31.8	41.3		ne, Gray						
41.3	42.8								
71.0	76.0	JHUIC,	~ · · · · · · · · · · · · · · · · · · ·						
			A.A. 190. AMV. C.	California de la companya del companya del companya de la companya				A. A. J. Marine 1997	
1 601-	ACTORIO (	D   ANDOME	DIS OFFICE	TIONI. This water we'll	4100 (1) Donat	eted (2) ===	onetruoted or //	3) plugged up	der my jurisdiction and was
I CONTR	AUTUR'S C	TH LANDOWNE	no CERTIFICA 2/01	HON: This water well	wascijconstru	ond this res	ord is true to the	back of my kn	owledge and belief. Kansas
ompleted (	on (mo/day/	year) LU/.	<i>И</i> 16	This Water	Moll Booss ::	and this fect	on (mo/dou/u-\	best of my kn	/
					vven mecora wa			1 /m	Vel
under the b	usiness nar	ne or lerra	con Consul	Calles JL		by (signa	ature) 2	~~ "/	NATURE OF THE PARTY OF THE PART