WATER WELL RECORD Form WWC-5					Div	vision of Wate	er Resources App. N	O.	
1 LOCATION OF WATER WELL:			Fraction	1	l l	on Number	Township No.	Range Number	
County: Dickinson			1/4 SW 1/4 SW		31 T 11 S R 2 K E W				
	Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:		
	from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
1 mile North & 1/2 mile East of Talmage, KS						Elevation:			
W AAAYU	CINCINC NOTO	TW. W. SANK TWY TRY TO			<u>Datum</u>	ı: 🔲 WGS 8	4, □ NAD 83, □] NAD 27	
2 WATER WELL OWNER: Larry Bathurst RR#, Street Address, Box #: 771: 3100 Ave.						Collection Method:			
RR#, Street Address, Box #: 771: 3100 Ave. City, State, ZIP Code : Abilene, KS 67410						☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City,	State, Z	a code . ADITEI	IE, KS 0/410					5-15 m, \square >15 m	
3. LOCATE WELL.									
!	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 90 ft.								
SECI	SECTION BOX: N Depth(s) Groundwater Encountered (1)								
	Pump test data: Well water was								
12-15 xx 11 (0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								nninggpm	
WNW NE EST. YIELD								.ft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								Injection well	
SWSE									
Irrigation Industrial Domestic-lawn & garden Monitoring well									
h-va-recoverage	was a chemical/bacteriological sample submitted to Department? [] Yes K No								
S If yes, mo/day/yr sample was submitted Water well disinfected? X Yes No									
water wen disinfected: [25 Fes] No									
5 TYPE OF CASING USED: Steel X PVC Other Other									
Casing digmeter 5 in to 50 ft Digmeter in to ft Digmeter in to ft									
CASING JOINTS: X Glued Clamped Welded Threaded Casing diameter 50 in. to 50 ft., Diameter in. to									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From. 50 ft. to 90 ft., From ft. to ft.									
From									
GRAVEL PACK INTERVALS: From. 25 ft. to90 ft., From ft. to ft.									
From									
Grout Intervals: From									
i		est source of possible conta							
X Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well Direction from well Distance from well Feedyard F									
Direc	Watertigi tion from	nt sewer lines West Seepage p	oit	Fertilizer	storage from w	11 60 ft.	as well		
FROM	TO	LITHOLOG	HC LOG	FROM	TO	LITHO I	OG (cont.) or PLI	UGGING INTERVALS	
0	2	Topsoil		81	90	Shale,		The second secon	
2	9	Clay, brown							
9	20	Clay, tan							
20	40	Shale, tan w/lime	estone layers						
40	42	Shale, green				and the formula the control of the c			
42	45	Shale, red		-					
45 60	60 61	Shale, gray Shale fracture							
61	80	Shale fracture Shale, gray							
80	81	Shale, fracture							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\bigsize \) constructed, \(\substact \) reconstructed, or \(\substact \) plugged									
under my jurisdiction and was completed on (mo/day/year) 3./26/12 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No 1.38 This Water Well Record was completed on (mg/day/yegr) 3/30/12									
under the business name of									
		Use typewriter or ball point per o Kansas Department of Health							
		5524. Send one copy to WAT							
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212									