

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Leavenworth	Fraction NE 1/4 SE 1/4 SE 1/4	Section number 11	Township number T 11 S R 21	Range number EW																																																
2. Distance and direction from nearest town or city: Street address of well location if in city: 2 miles east of Tonganoxie, Kansas			3. Owner of well: R.R. or street: City, state, zip code:																																																			
4. Locate with "X" in section below: Sketch map:			6. Bore hole dia. 8 in. Completion date 11-4-78 Well depth 100 ft.																																																			
			7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary																																																			
5. Type and color of material			8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr><td>Top Soil</td><td>0</td><td>3</td></tr> <tr><td>Clay</td><td>3</td><td>20</td></tr> <tr><td>Clay & Gravel</td><td>20</td><td>23</td></tr> <tr><td>Sandy Clay</td><td>23</td><td>31</td></tr> <tr><td>Sandstone - Yellow</td><td>31</td><td>33</td></tr> <tr><td>Sandy Shale</td><td>33</td><td>40</td></tr> <tr><td>Sandstone - Gray</td><td>40</td><td>58</td></tr> <tr><td>Lime</td><td>58</td><td>60</td></tr> <tr><td>Slate</td><td>60</td><td>63</td></tr> <tr><td>Lime</td><td>63</td><td>68</td></tr> <tr><td>Shale</td><td>68</td><td>74</td></tr> <tr><td>Lime</td><td>74</td><td>75</td></tr> <tr><td>Shale</td><td>75</td><td>87</td></tr> <tr><td>Lime</td><td>87</td><td>96</td></tr> <tr><td>Shale</td><td>96</td><td>100</td></tr> </tbody> </table>				From	To	Top Soil	0	3	Clay	3	20	Clay & Gravel	20	23	Sandy Clay	23	31	Sandstone - Yellow	31	33	Sandy Shale	33	40	Sandstone - Gray	40	58	Lime	58	60	Slate	60	63	Lime	63	68	Shale	68	74	Lime	74	75	Shale	75	87	Lime	87	96	Shale	96	100	9. Casing: Material PL Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 265 lbs./ft. Dia. 5 in. to 101 ft. depth Wall Thickness: inches or Dia. 5 in. to 101 ft. depth gage No. 265			
	From	To																																																				
Top Soil	0	3																																																				
Clay	3	20																																																				
Clay & Gravel	20	23																																																				
Sandy Clay	23	31																																																				
Sandstone - Yellow	31	33																																																				
Sandy Shale	33	40																																																				
Sandstone - Gray	40	58																																																				
Lime	58	60																																																				
Slate	60	63																																																				
Lime	63	68																																																				
Shale	68	74																																																				
Lime	74	75																																																				
Shale	75	87																																																				
Lime	87	96																																																				
Shale	96	100																																																				
			10. Screen: Manufacturer's name (Slotted Pipe) Vinylplex, inc. Type PVC Dia. 5" Slot/gauze 06 1/16 Length 18' Set between 40 ft. and 58 ft. ft. and 58 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4 - 1/8																																																			
			11. Static water level: 30 ft. below land surface Date 12-11-78 mo./day/yr.																																																			
			12. Pumping level below land surfaces: 30 ft. after 1 hrs. pumping 20 g.p.m. 30 ft. after 1 hrs. pumping 20 g.p.m. Estimated maximum yield 20 g.p.m.																																																			
			13. Water sample submitted: 12-11-78 mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date																																																			
			14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 18 Inches above grade																																																			
			15. Well grouted? Yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 3 ft. to 12 ft.																																																			
			16. Nearest source of possible contamination: horse barn ft. 100 Direction east Type barn Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																																																			
			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Jacuzzi Model number 554B HP 1/2 Volts 220 Length of drop pipe 90 ft. capacity 10 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																			
18. Elevation: 860 Topography: low <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley			19. Remarks:																																																			
			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BREUER, INC. 174 Business name License No. Address Box 147, Basehor, Ks. 66004 Signed Frank A. Breuer Date 1-7-79 Authorized representative																																																			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5