


1 LOCATION OF WATER WELL: County: Leavenworth Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 27 Township Number: T 11 S Range Number: R 31 EW

Distance and direction from nearest town or city street address of well if located within city?
3m South of Tonganoxie.

2 WATER WELL OWNER: Bill Garner Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 915 S. Church Tonganoxie, KS 66086 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 147 ft. ELEVATION: 105 ft. below land surface measured on mo/day/yr 6-25-88
 Depth(s) Groundwater Encountered 1. 135 ft. 2. 6 1/2 ft. 3. 147 ft.
 Pump test data: Well water was 4 ft. after 8 hours pumping 4 gpm
 Est. Yield 4 gpm: Well water was 8 ft. after 26 hours pumping 6 1/2 gpm
 Bore Hole Diameter: 8 in. to 26 ft., and 6 1/2 in. to 147 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 100 ft., Dia. 24 in. to SPR 26 lbs./ft. Wall thickness or gauge No. SPR 26
 Casing height above land surface: 24 in., weight SPR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 10 PVC
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 107 ft. to 147 ft. From 107 ft. to 147 ft.
 GRAVEL PACK INTERVALS: From NO ft. to NO ft. From NO ft. to NO ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 32 ft. From 32 ft. to 100+ ft.
 What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Underground
 13 Insecticide storage
 Direction from well? How many feet? 100+

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	TS			
2	20	Clay yellow			
20	30	shale			
30	33	Lime			
33	135	shale			
135	147	SS. Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-88 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 216 This Water Well Record was completed on (mo/day/yr) 6-26-88
 under the business name of Robison Pulling by (signature) Jack Robison

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.