White—Driller's Copy
Blue—Kansas Geological Survey
Pink—Customer Copy

11-21-19 bc

WATER WELL RECORD

DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	4	Topsoil
4	18	Clay and Rocks
18	24	Clay and Gravel
24	30	Gravely Shale
30	78	Sandy Shale

Well Owner: L. W. Baird
Address: Tonga. Kansas
Drilling Contractor: Breuer Drilling Co.
Date Drilled: Sept. 8, 1956
Method of Drilling: Cable tool
Casing: Used Steel 6¼ & 4 7/8
(New, Used—Steel, Galv.—Gage or Weight)
Casing Schedule: 34 ft. 6¼ 49ft. 4 7/8
(Amount, Size, Setting)
Screen Data (if any):

ON COMPLETED WELL

Measured depth to water (Static Level) is 20 ft.
below land surface
(Land Surface, Top of Casing, Etc.)
TESTED YIELD: 60 gallons per hr
(Min., Hour)
as determined by bailing
(Bailing, Test Pumping, Etc.)
DRAWDOWN: ft. after hrs.
pumping at gal. per minute.

REMARKS:

LOCATION OF WELL
[Show location in Section Plat]

Elev. ±920



SW ¼ NW ¼ Sec. 19
T. 11 S., R. 21 E.
County Leavenworth

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

26-1633-S—27-32 11-55-3M SETS