White—Driller's Copy
Blue—Kansas Geological Survey
Pink—Customer Copy

13RT

WATER WELL RECORD

DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	2	Topsoil
2	4	Clay
4	6	Sandstone yellow
6	30	Clay yellow
30	107	Sandy Shale
107	111	Sandstone
111	120	Sandy shale
120	145	Sandstone WATER-
145	150	Lime
	150	T.D.

Well Owner: John Grafe

Address: Tonga., Kansas

Drilling Contractor: Breuer Drilling Co.

Date Drilled: March 19, 1957

Method of Drilling: Cable Tool

Casing: Used Steel 6 (New, Used—Steel, Galv.—Gage or Weight)

Casing Schedule: 127ft. (Amount, Size, Setting)

Screen Data (if any):

ON COMPLETED WELL

Measured depth to water (Static Level) is 75 ft. below land surface (Land Surface, Top of Casing, Etc.)

TESTED YIELD: 9 gallons per min (Min., Hour) as determined by Bailing (Bailing, Test Pumping, Etc.)

DRAWDOWN: ft. after hrs. pumping at gal. per minute.

REMARKS:

Good Well

TOPKA

LOCATION OF WELL [Show location in Section Plat]

Tonganoxie 7½

Elev. 920

NE NE ¼ SW ¼ Sec. 22

T. 11 S., R. 21 E. W.

County Dear

BR=916

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

26-1633-S—27-32 11-55-3M SETS

Σ = 545