USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Me 1 1800 0

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

						Topeka, Nansas 00020	
	County	Fraction		Section		Township number Range number	
1. Location of well:	Leavenworth	NW 1/4 NW 1/4 SE	1/4	8	3	T 11 S R 22 (E)W	
2. Distance and direc	tion from nearest town or city: 12	miles east	3. Own	er of well	:	Mr. Myron Blackburn	
Street address of well location if in city: Of Tonganoxie, Ks. R.R. or street:						3236 North 63rd	
City, state, zip code					ode:	Kansas City, Kansas 66104; 6. Bore hole dia 8 in. Completion date 6-30- Well depth 120 ft.	
4. Locate with "X" in section below: N Sketch map:						Well depth 120 ft.	
						7 Cable tool X Rotary Driven Dug	
NW NE						Hollow rod Jetted Bored Reverse rotary	
w 1 1 1 E						8. Use: X Domestic Public supply Industry	
S W SE						Irrigation Air conditioning Stock Lawn Oil field water Other	
						9. Casing: Material PL: Height: Above or below	
						Threaded Welded Surface in.	
						RMP PVC X Weight lbs./ft. Dia. 6 in. to 50 ft. depth Wall Thickness: inches or	
5. Type and color of material				From	То	Dia in. to ft. depth gage No 280	
	19.					10. Screen: Manufacturer's nameNONE	
Top Soil				0	1	Type Dia	
Clay - Y	Cellow			ı	5	Slot/gauze Length	
				-		ft. andft.	
Sandstone - Yellow				5	9	Gravel pack? Size range of material	
Lime - White				9	10	11. Static water level: mc./day/yr.	
Sandstone - Yellow				10	12	12. Pumping level below land surfaces:	
***************************************				12	19	ft. after hrs. pumping g.p.m.	
Shale - Blue						ft. after hrs. pumping g.p.m. Estimated maximum yield 3 g.p.m.	
Sandy Shale - Blue				19	26	13. Water sample submitted: mo./day/yr.	
Santstone - Gray				26	31	Yes X No Date	
Sandy Shale - Blue				31	35	14. Well head completion: X Pitless adapter 18 Inches above grade	
Sandy Share - Ditte				71		15. Well grouted? Yes	
Sandstone - Gray				35	73	With: X Neat cement Bentonite Concrete Depth: FromO ft. to50_ ft.	
Lime - White				73	85		
				1.5		16. Negrest source of possible contamination: ft. 600 Direction South Type septic	
Slate - Black				85	90	Well disinfected upon completion? X Yes No	
Lime - White				90	94	17. Pump: Not installed Jacuzzi	
Shale - Blue				94	106	Model number 554B HP 1/2 Volts 220	
Lime - Brown				106	107	Length of drop pipe 65 ft. capacity 10g.p.m. Type:	
Shale - Blue				107	11/4	Tot bille	
Iime - V	Vhite (Use a second s	heet if needed)		114	120	Jet Reciprocating Other	
18. Elevation:	19. Remarks:					20. Water well contractor's certification:	
WELL SHOT AT 72 FT. 1 GALLON PER					This well was drilled under my jurisdiction and this report		
Topography: MINUTE BEFORE SHOT, 3 GALLON AFTER					is true to the best of my knowledge and belief. BREUER. TNC. Box 14		
HIII					الملا	Business name License No.	
Slope Upland						Address H V VIII MANIN Ach	
Valley						Signed Date Date Date	
orward the white, blue	e and pink copies to the Department	of Health and Environment				Form WWC-5	