

Located <sup>or</sup> Top-Kan  
 Study map

11-22-20 da  
 no map/entry  
 entered in comp. b.  
 V B R T

# WATER WELL RECORD

## DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	2	Top Soil
2	40	Sandy Clay Little water at Bottom
40	85	Sandy Shale
85	90	Lime
90	95	Shale
95	115	Lime
115	119	Shale Dark Slate
119	122	Lime
122	135	Sandy Shale
135	145	Shale
145	163	Lime
163	167	Shale Red Bed
167	185	Shale
185	192	Lime
192	197	Shale
197	212	Lime
212	217	Shale
217	263	Lime <i>any</i>
263	265	Shale
265	271	Lime
271	275	Shale Slate Little <sup>water</sup> *****
275	285	Shale
285	300	Lime
300	304	Shale Dark
304	314	Shale Sandy

Well Owner L. Clinite  
 Address Bonner Springs  
 Drilling Contractor Brauer Drilling Co.  
 Date Drilled \_\_\_\_\_  
 Method of Drilling Cable Tool  
 Casing: 6 1/4 Steel 1 1/2  
(New, Used Steel, Galv. — Gage or Weight)  
 Casing Schedule: \_\_\_\_\_  
(Amount, Size, Setting) -  
317 ft. 6 1/4 Steel  
 Screen Data (if any): \_\_\_\_\_

### ON COMPLETED WELL

Measured depth to water (Static Level) is 35 ft.  
 below Land surface  
(Land Surface, Top of Casing, Etc.)  
 TESTED YIELD: \_\_\_\_\_ gallons per \_\_\_\_\_  
(Min., Hour)  
 as determined by \_\_\_\_\_  
(Bailing, Test Pumping, Etc.)  
 DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.  
 pumping at \_\_\_\_\_ gal. per minute.

### REMARKS:


Approx 70 ft. water overnight

~~BR 910~~  
~~BR 911~~

### LOCATION OF WELL

[Show location in Section Plat]

951  
 Elev. 913



SE NE 1/4 SE 20  
 T. 11 S.; R. 22 E.  
 County Worth

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."



Plotted Strip Log