

1 LOCATION OF WATER WELL: County: LEAVENWORTH	Fraction SE 1/4 SE 1/4 SW 1/4	Section Number 33	Township Number T 11 S	Range Number R 22 E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 1/2 east, 3 1/4 north of Linwood

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	John Fitzgibbon 17042 Stillwell Rd. Bonner Springs, KS 66012	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 120' ft. ELEVATION:
--	---

N

NW	NE
SW	SE

S

X

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL **43'** ft. below land surface measured on mo/day/yr **05/26/98**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **4** gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: **8 3/4** in. to ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No **X**; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5" in. to 0-40 ft., Dia 5" in. to 80-119 ft., Dia in. to ft.			
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No.258			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 40 ft. to 80 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 119 ft. to 120 ft., From ft. to ft.			
From 24 ft. to 120 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? east				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? 420'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	Clay-Brown			
12	14	Sandstone-Brown			
14	23	Shale-Yellow			
23	43	Shale-Grey			
43	53	Sandstone-Brown			
53	57	Limestone-Grey			
57	61	Shale-Grey			
61	64	Limestone-Grey			
64	65	Shale-Grey			
65	82	Limestone-Grey			
82	86	Shale-Black			
86	94	Limestone-Grey			
94	112	Shale-Grey			
112	120	Limestone-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/26/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 6-3-98 by (signature) Dale Askron under the business name of STRADER DRILLING CO., INC.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone. 913-296-5545. Send one to WATER WELL OWNER and retain one for your records

OFFICE USE ONLY