

See Top Kaw map  
 77  
 JB  
 Raw

# WATER WELL RECORD

## DRILLERS LOG OF WELL

Well Owner Roye Hill

Well Owner \_\_\_\_\_

Address \_\_\_\_\_

Drilling Contractor Breuer drilling Co.

Basehor, Kansas Co.

Date Drilled 1/15/67

Method of Drilling Cable Tools  
 (Cable tool, rotary, reverse rotary, etc.)

Casing Schedule None  
 (Amount, Size, Setting—New, Used—Steel, Galv.—Gage or Weight)

Screen Data (if any): \_\_\_\_\_  
 (Length, Diameter, Slot Size, Setting)

Measured depth to water on completed well (Static Level) is \_\_\_\_\_  
 ft. below \_\_\_\_\_  
 (Land Surface, Top of Casing, Etc.)

TESTED YIELD: \_\_\_\_\_ gallons per \_\_\_\_\_  
 (Min., Hour)


as determined by \_\_\_\_\_  
 (Bailing, Test Pumping, Etc.)

DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.

pumping at \_\_\_\_\_ gal. per minute.

REMARKS:

LOCATION OF WELL Topographic Sheet Banner Springs  
 [Show location in Section Plat] Elev. \_\_\_\_\_



SW  $\frac{1}{4}$  SE  $\frac{1}{4}$  Sec. 5

T. 11 S., R. 22 E. W.

County Raw

#1 BR = 856  
 #2 BR = 870

862  
 DBE  
 BR = 858

875  
 870  
 PCD

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
		Test No. I N W Cor.
0	2	Top Soil
2	4	Clay
4	16	Sandy Stone
16	23	Shale
23	37	sandy shale S.L. 39ft.
37	55	Sand stone water 1/2 G.P.M.
55	63	Shale
63	74	Lime
74	75	Shale T. D. 75 ft.
		Test no 2 Appox 500ft East of House
0	3	Top Soil
3	25	Clay APPOX: 25 G.P.M.
25	39	Shale
39	62	Sandy Shale
62	68 1/2	Sand stone
68 1/2	70	Lime
70	75	Lime Shale
75	78	Sandy shale
78	81	Gravel Shale
81	83	Lime T. D. 83ft.

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."