

VBR

WATER WELL RECORD

DRILLERS LOG OF WELL

1854
 BR-819
 40'

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	2	Top Soil
2	5	Clay
5	15	Sandstone Yellow
15	16	Shale
16	26	Sandstone Yellow
26	34	Sandstone Gray
34	45	Lime
45	49	Black Slate
49	53	Lime
53	73	Shale
73	87	Lime
87	92	Shale
92	97	Red Shale
97	114	Shale
114	122	Lime
122	124	Shale
124	125	Lime T. D. 125 ft.
		Test No. 2
0	2	Top Soil 23 1/2 24 sandy Shale
2	10	Clay 24 26 sandy Shale Gray 26 30 Sandstone Yellow
10	16	Sandstone Yellow 30 38 Sandstone Gray 38 Lime
16	20	Shale Gray Sandy 38 T.D.
20	22	Sandstone Yellow
22	23	Gray sandy shale
23	23 1/2	sandstone gray

24
 26
 BR-850
 W-2

Well Owner Mr. Buster Dowing

Address Basehor, Kansas

Drilling Contractor Breuer Drilling Co.
Basehor Kansas

Date Drilled 1/10/72

Method of Drilling Air Rotary
 (Cable tool, rotary, reverse rotary, etc.)

Casing Schedule 20 ft Plastic
 (Amount, Size, Setting—New, Used—Steel, Galv.—Gage or Weight)

Screen Data (if any): _____
 (Length, Diameter, Slot Size, Setting)


Measured depth to water on completed well (Static Level) is
24 ft. below Land Surface
 (Land Surface, Top of Casing, Etc.)

TESTED YIELD: 1/2 gallons per Min
 (Min., Hour)
 as determined by Bailing
 (Bailing, Test Pumping, Etc.)

DRAWDOWN: _____ ft. after _____ hrs.
 pumping at _____ gal. per minute.

REMARKS:
Well Shot
1/4 gal. before
1/2 gal. after
Storage Approx 500 gals

LOCATION OF WELL Topographic Sheet Tonganmoo
 (Show location in Section Plat) Elev. 855 ± 5



T. 11 S., R. 22 E. W.

County Reno
 BR-845
 2-826

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."