		WATE	R WELL RECORD	Form WWC-	KSA 82a	-1212			
LOCATION OF WATER WELL:		Fraction	SE 14 SE		ction Number	Township	Number	Range Nun	200
			ddress of well if locate		<i></i>	T /	(8)	H A	Ow.
<i>C</i>	S. Lu D	Bonn		-					
2 WATER WELL O	WNED.	1 11.0				mw	2 #168	340	
RR#, St. Address, B	1 174	int Her	n + stre	-			f Agriculture, Divi	•	Recourse
City, State, ZIP Code	1.4	SET	-cont-stre		- <		ion Number:	Sion of water	nesource
3 LOCATE WELL'S		15 6n	Me Spin	12/0	5 51511			· · · · · · · · · · · · · · · · · · ·	
AN "X" IN SECTION	NI BOV.		OMPLETED WELL		7). π. ELEVA	TION:			
-	N DE	epin(s) Ground	water Encountered	น์ติ	Τοςπ. 2	.	ft. 3.	Tii lai	ft.
1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1		WATER LEVEL . 1.7						
NW	NE _	Pump	test data: Well water	er was	ft. a	fter	hours pump	ing	gpm
1 1	l Es	t. Yield	gpm: Well water	er was	ft. a	fter	hours pump	ing	gpm
* w			terin. to			and	in. to		ft.
≦	1 ! W	ELL WATER T	O BE USED AS:	5 Public water		8 Air conditioni	ng 11 Inje	ection well	
I sw	SE 4 -	1 Domestic		6 Oil field wa		9 Dewatering	12 Oth		
1 1	$ \mathcal{X} $	2 Irrigation					ell		
ļ <u>L · </u>	l Wa	as a chemical/b	acteriological sample s	submitted to D	epartment? Ye	s	; If yes, mo	/day/ <u>vr_s</u> ample	e was sub
<u> </u>	S mi	tted				ter Well Disinfe		No	
5 TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING .	OINTS: Glued	Clamped	d
Steel	3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify below	v)	Welded .		
2) VC	A ABS	~'s	7 Fiberglass				Threade	d <i></i>	
-	r in.	to J Q. L.	٩L ft., Dia	in., to		ft., Dia	in.	to	ft.
Casing height above	land surface	ł.7	in., weight		lbs./	ft. Wall thicknes	s or gauge No.		
TYPE OF SCREEN (OR PERFORATION M	MATERIAL:		7 PV	`		sbestos-cement		
1 Steel	3 Stainless st	eel	5 Fiberglass	8 RM	IP (SR)	11 C	ther (specify)		
2 Brass	4 Galvanized	steel	6 Concrete tile	9 AB	S		one used (open		
SCREEN OR PERFO	RATION OPENINGS	ARE:	5 Gauze	ed wrapped		8 Saw cut	٠.	None (open	hole)
1 Continuous sl	ot 3 Mill s	lot	6 Wire	wrapped		9 Drilled hole		(,
2 Louvered shu	tter 4 Key p	ounched	7 Torch	cut		10 Other (spec	;ify)		
SCREEN-PERFORAT	ED INTERVALS:	From	. 8 ft. to	1.%	ft., Fror	n	ft. to		ft
		From	ft. to		ft Fror	n	ft to		ft
GRAVEL PA	ACK INTERVALS:	From	7 ft. to	1.8	ft., Fror	n	ft. to		ft
		From	ft. to		ft., Fron		ft. to		ft.
GROUT MATERIA	L: 1 Neat cem	ent	Cement grout	3 Bento	nite 4	Other			
Grout Intervals: Fro	omft.	to	ft., From 5.						
	ource of possible con				10 Livest			doned water w	
1 Septic tank	1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines	2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)		
3 Watertight set	ver lines 6 Seepage	9 Feedyard	13 Insecticide storage			usts	(0,000)	,	
Direction from well?	, 5	•			How man	•			
FROM TO		LITHOLOGIC L	.OG	FROM	ТО	,	PLUGGING INTE	RVALS	
0 2	Topsoil								
5 7	SH, Cla	arou.	iron Stains						
10 12	Sand 7	ine-me	•						
13 15	Sand, 7	ini - med,	gon						
18.5 20	Sheli R	m.wa	theres						
				-					
	<u> </u>								
CONTRACTOR'S	OR LANDOWNERIS	CERTIFICATIO	N: This water well we	s (1) constru	cted, (2) recor	nstructed, or (3)	plugged under r	ny jurisdiction	and was
completed on (mo/day	/year) 🎜 🛴	111			and this recor	u is true to trie i	est of my knowle	dge and belief	. Kansas
Water Well Contractor	's License No 🎻		This Water We	ell Record wa	s completed o	n (mo/day/yr)			
under the business na	me of	ST			by (signati	ire)	1601-	_	
			MLY and PRINT clearly. Plea					s to Kansas Depar	rtment