HWIZ

WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Wyandottl	Fraction SE 1/4 SE 1/4 SW 1/4	Section Number Township No. Range Number T S R Z3 ME W
Street/Rural Address of Well Location;		Global Positioning System (GPS) information: Latitude:39
from nearest town or intersection: If at		Latitude:
13844 State Aue - Bonn	el Springo, Ks.	Elevation: .4.7.4 s.5D
2 WATER WELL OWNER: JHK	Partnership	Datum: WGS 84, NAD 83, NAD 27 Collection Method:
RR#, Street Address, Box #: / 1700	Beilles Company	GPS unit (Make/Model:)
RR#, Street Address, Box #: City, State, ZIP Code : 608	iselatuare Wenuvocal Ks. idea 48	☐ Digital Map/Photo, ☐ Topographic Map, 【X Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
2 TOCATE WELL		
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 30'	
SECTION BOX: Depth(s) Ground WELL'S STAT	Iwater Encountered (1)	ft. (2) ft. (3) ft. below land surface measured on mo/day/yr. 1/30/12
WELL'S SIAI	tost date: Wall water was	ft. after hours pumping gpm
FST VIELD	riest data. Well water was	ft after hours numning onm
W - NW NE - EST. YIELD	wheter $7b'$ in to $3b'$ fi	ft. after hours pumping gpm t., andin. toft.
WELL WATER	TO BE USED AS: Public water	er supply
swse Domestic	☐ Feedlot ☐ Oil field wate	er supply
		vn & garden X Monitoring well
Was a chemical	bacteriological sample submitted to	Department? Yes No
S If yes, mo/day/yr sample was submitted		
1 mile Water well disir	ifected? Yes X No	
5 TYPE OF CASING USED: Steel 🗵 PVC 🗆 Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter 2.375 in to 15 ft., Diameter in to ft., Diameter ft., Diameter ft., Diameter ft.		
Casing height above land surface Fush Mt in., Weight		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched	☐ Wire wrapped ☐ Saw cut	Other (specify)
SCREEN-PERFORATED INTERVALS:	From. 3D ft. to 15	ft., From ft. to ft.
From		
GRAVEL PACK INTERVALS: From		
From		
Grout Intervals: From 13. ft. to 2. ft., From ft., From ft., From ft.		
What is the nearest source of possible cont		to to the fact that the total the to
	nes Pit privy Livestock p	bens Insecticide storage
Sewer lines Cesspool	Sewage lagoon Fuel storage	e Abandoned water well Storm Water
	oit Feedyard Fertilizer st	orage Oil well/gas well
Direction from well . South		from well .70.
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
D 2.5 Lary aguel, de		
	mp	
	amo da dano	
10.0 14.0 LBW fine-MAD		200
20.0 24.0 Wed Byn-Red	sixhou and fore and	(n 1 T X
24.0 25.0 Red Bun and St	ma with	0000
	na well cemented fi	regionel with
LINE S. C. LELICHICHER	in jackson was, jus	Je spanish de si jaren de la companya de la company
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water	er well was 🔀 constructed, 🗌 reconstructed, or 🔲 plugged
under my jurisdiction and was completed on (mo/day/year)		
Kansas Water Well Contractor's License No This Water Well Record was completed on (mo/day/year) 2/10/12		
under the business name of Checoo	non-yertal	by (signature) Ames GUREU
		early. Please fill in blanks and check the correct answers. Send three copies
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		