	HWIT				
WATER WELL RECORD	Form WV		-	r Resources App. N	
1 LOCATION OF WATER WELL: County: Wyandotte	Fraction NE 1/4 NE		ection Number	Township No.	Range Number R <b>23 X</b> E □W
Street/Rural Address of Well Location;	f unknown, distance &	direction GI	obal Positioning	System (GPS) is	nformation:
from nearest town or intersection: If at o		nere []. La	atitude: 2.4 I.	1539 90010	(in decimal degrees) (in decimal degrees)
13844 State Aul; Kan	sau lity, Ks versprugs, Ks	, El	evation:958	. ب	
2 WATER WELL OWNER: JMK 1	utrushio	$\overline{C}$	atum: [] WGS 84 ollection Method:	4, 🗌 NAD 83, 🗀	NAD 27
	Reilly Compan		Digital Map/Ph	oto, 🗌 Topographi	) c Map, 🔏 Land Survey
3 LOCATE WELL   Leavenworth K5 Loled 48   Est. Accuracy:   <3 m,   3-5 m,   5-15 m,   >15 m					
with an "x" in 4 DEPTH OF COMPLETED WELL 22.9. ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1).107					
WELL'S STATIC WATER LEVEL. 1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1					
EST. YIELDgpm. Well water was					
W   E   Bore Hole Diameter . 1. 2. in. to					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well  Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
SWSE   Domestic   Feedlot   Oil field water supply   Dewatering   Other (Specify below)   Industrial   Domestic-lawn & garden   Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted Water well disinfected?  Yes No					
5 TYPE OF CASING USED: Steel N PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter 3.3.75 in. to 12 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface Fully Mb. in., Weight lbs./ft., Wall thickness or gauge No. 50, 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)					
Brass Galvanized Steel None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)					
SCREEN-TEATORATED INTERVALS.	Fromft	to	ft., From	ft.	to ft.
GRAVEL PACK INTERVALS:	From <b>22.9</b> ft	to 10.9	ft., From	ft.	to ft.
	From ft.		ft., From  Other Lan	ft.	to ft.
6 GROUT MATERIAL: Neat cemes Grout Intervals: From	nt Cement grout	Bentonite  ft to			ft to ft
What is the nearest source of possible conta				110111	10. 00
Septic tank Lateral lin		Livestock pens	Insecticide		ner (specify below)
Sewer lines Cesspool Watertight sewer lines Seepage p	Sewage lagoon it Feedyard	] Fuel storage ] Fertilizer storag		water well sto	u Arans
Direction from well South.		Distance from	well		
FROM TO LITHOLOG	L	FROM TO	LITHO. LO	OG (cont.) <u>or</u> PLU	JGGING INTERVALS
0 1.0 Red sandy sit					
2.0 3.0 Leandan dam					
3.0 5.0 DKBenclay, dan	φ				
5.0 6.5 DKRERBERTINE	rgines sorg	2 4 4 4			
8.0 15.0 led Bur weather	in populations	one HOLD	<b>x</b>		
15.0 16.5 Lt. Red Bungands	IND WID	ene pour			
165 200 Howweathered	panalstone u	YD .			
200 229 En weathered anastore wet					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🕱 constructed, 🗌 reconstructed, or 📗 plugged under my jurisdiction and was completed on (mo/day/year)					
Kansas Water Well Contractor's License No. 133 This Water Well Record was completed on (mo/day/year)					
under the business name of ABEN W	nmental	by	(signature)	amas Burb	(L)
INSTRUCTIONS: Use typewrite for ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WAT http://www.kdheks.gov/waterwell/index.html.	ER WELL OWNER and re	ain one for your r	ecords. Include fee	of \$5.00 for each	constructed well. Visit us at
KSA 82a-1212					