

White—Driller's Copy  
Blue—Kansas Geological Survey  
Pink—Customer Copy

11-23-6 ab

Clinton Road  
13739 Parrot

BRT

# WATER WELL RECORD

## DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	2	Top Soil
2	43	Sandrock Water 2 Gal. min.
43	46	Lime
46	50	Shale
50	68	Lime
68	78	Shale Dark
72	76	Lime Hard
76	82	Shale
82	106	Lime
106	110	Shale T.D.

Well Owner B. b. Martainetz  
Victory Jct.

Address \_\_\_\_\_

Drilling Contractor Breuer Drilling Co.

Date Drilled 8 1955

Method of Drilling Cable Tools

Casing: 8 in. Approx. 7 ft. Used  
(New, Used—Steel, Galv.—Gage or Weight)

Casing Schedule: \_\_\_\_\_  
(Amount, Size, Setting)

Screen Data (if any): \_\_\_\_\_

### ON COMPLETED WELL

Measured depth to water (Static Level) is 30 ft.  
below Land Surface  
(Land Surface, Top of Casing, Etc.)

TESTED YIELD: 2 gallons per min  
Bailing (Min., Hour)

as determined by \_\_\_\_\_  
(Bailing, Test Pumping, Etc.)

DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.  
pumping at \_\_\_\_\_ gal. per minute.

### REMARKS:

TOP Kan Map

LOCATION OF WELL

[Show location in Section Plat] Elev. 745

NW NW x NE NE Sec. 6

T. 11 S., R. 23 W.

County Wyo

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

X (C) Plotted Log

Both #  
R223  
Not correct 5-10-73

KANSAS WELL SCHEDULE

Card 1

Record by Klaus 15-10 Project: top-KC State: Kan County: Wydt

Latitude: \_\_\_\_\_ Longitude: \_\_\_\_\_ Accuracy: \_\_\_\_\_ Owner's well no: \_\_\_\_\_

Location: NW 1/4 no. sec. 6, T. 11 N., R. 23 E. Well number: 1123E 6ABB

Owner: Clinton Roach name address Victory Jet 13739 Parallel

Owner: \_\_\_\_\_ Altitude: 945 Accuracy: 3

Driller: Brauer name address \_\_\_\_\_ Date drilled: 1955

Topography, well site: (D) Draw, (F) flood plain, (L) lowland, (R) rolling, (S) slope, (T) terrace, (U) upland \_\_\_\_\_ Spring; or depth of well: 110 feet \_\_\_\_\_

Diameter: 8" inches or feet \_\_\_\_\_ Depth cased: 7 feet \_\_\_\_\_ Spring, or Csg. type: stud \_\_\_\_\_ Finish: \_\_\_\_\_ Lift & power: submeter \_\_\_\_\_

Pump setting: \_\_\_\_\_ Use of well: Domestic, stock, irrigation, industrial, public supply, observation, none, test \_\_\_\_\_

Water level: 19.7 feet \_\_\_\_\_ above \_\_\_\_\_ below \_\_\_\_\_ date measured: 9-10-73 \_\_\_\_\_ Water level records avail. \_\_\_\_\_

Description MP: Top casing 2' 0" below surface in Block enclosure \_\_\_\_\_

Yield: 2 gpm \_\_\_\_\_ Pumping period: \_\_\_\_\_ Specific capacity: \_\_\_\_\_

Pumpage and other data available: \_\_\_\_\_

Card 2

Coefficient trans: \_\_\_\_\_ Coefficient storage: \_\_\_\_\_ Coefficient perm.: \_\_\_\_\_

Aquifer, system or series \_\_\_\_\_ Aquifer, units: Douglas \_\_\_\_\_ Strawn \_\_\_\_\_

Aquifer, thickness: \_\_\_\_\_ Aquifer, length of well open to: \_\_\_\_\_ Aquifer, depth to top of: \_\_\_\_\_ Aquifer, origin: \_\_\_\_\_

Aquifer, lithology of: SS \_\_\_\_\_

Bedrock, system: \_\_\_\_\_ Bedrock, formation: \_\_\_\_\_ Bedrock, depth to: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Log data avail: \_\_\_\_\_

Quality of water data available: \_\_\_\_\_ Temperature of water: \_\_\_\_\_ Date sampled: \_\_\_\_\_

Coefficient of leakage \_\_\_\_\_

THE FOLLOWING DATA ARE USED ON THE NATIONAL WELL SCHEDULE  
Ownership category: (C) County, (F) Federal Gov't., (M) City, (N) Corp. or Co., (P) Private, (S) State Agency, (W) Water Dist. \_\_\_\_\_

Method drilled: (A) Air, (B) bored, (C) cable, (D) dug, (V) driven, (H) hyd. rotary, (J) jetted, (R) rev. rotary, (T) trenching, (S) spring, \_\_\_\_\_

Physiographic province: \_\_\_\_\_ Section: \_\_\_\_\_

Drainage basin: \_\_\_\_\_ Subbasin: \_\_\_\_\_ Depth to basement: \_\_\_\_\_ source of data (basement) \_\_\_\_\_

Quadrangle \_\_\_\_\_  
Well no. 11-23E-6ABB

20'0  
2.3  
17.7  
+2  
19.7

102mg  
elec  
Jet