

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number	
County: WYANDOTTE	NE 1/4 SE 1/4 NE 1/4	1	T 11 S	R 24 EW	
Distance and direction from nearest town or city street address of well if located within city? South west Corner of 47th St. & Parallel, Kansas City, Kansas					
2 WATER WELL OWNER: AMOCO CORPORATION					
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number: NA			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 8.5 ft. ELEVATION: NA			
		Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft.			
		WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 5/8/97			
		Pump test data: Well water was 8 ft. after 8 hours pumping 8 gpm			
		Est. Yield 8 gpm: Well water was 8 ft. after 8 hours pumping 8 gpm			
		Bore Hole Diameter 7 in. to 7 ft., and 7 in. to 7 ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recovery Well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued No Clamped No					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded No Threaded X					
Blank casing diameter 4 in. to 4.5 ft. Dia 4.5 in. to 4.5 ft. Dia 4.5 in. to 4.5 ft.					
Casing height above land surface 12 in. weight 12 lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 4.5 ft. From 8.5 ft. to 4.5 ft. From 8.5 ft. to 4.5 ft.					
GRAVEL PACK INTERVALS: From 8.5 ft. to 4.0 ft. From 8.5 ft. to 4.0 ft. From 8.5 ft. to 4.0 ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 8.5 ft. to 4.0 ft. From 8.5 ft. to 4.0 ft. From 8.5 ft. to 4.0 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet? 150'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	CONCRETE			
1.0	5.0	Gr. Br. Silty Clay			
5.0	8.5	Highly weathered Limestone			
	8.5	Limestone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/8/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 602 This Water Well Record was completed on (mo/day/yr) 5/8/97 under the business name of Hydro-LOGIC, Inc. by (signature) Stephen P. Latham					