

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WYANDOTTE		NE 1/4 SE 1/4 NE 1/4	1	T 11 S	R 24 E
Distance and direction from nearest town or city street address of well if located within city?					
SOUTHWEST CORNER OF 47TH ST & PARALLEL, KANSAS CITY, KANSAS					
2 WATER WELL OWNER: AMOCO CORPORATION					
RR#, St. Address, Box # :			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			Application Number: N/A		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 11.0' ft. ELEVATION: N/A			
		Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft.			
		WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 5/8/97			
		Pump test data: Well water was 8 ft. after 8 hours pumping 8 gpm			
		Est. Yield 8 gpm: Well water was 8 ft. after 8 hours pumping 8 gpm			
		Bore Hole Diameter 7 in. to 7 in. and 7 in. to 7 in.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well					
2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)					
RECOVERY WELL					
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X					
Blank casing diameter 4 in. to 6.0 ft. Dia. 4 in. to 4 ft. Dia. 4 in. to 4 ft.					
Casing height above land surface 12 in. weight 40 lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)					
7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 11.0' ft. to 6.0' ft. From 6.0' ft. to 6.0' ft.					
GRAVEL PACK INTERVALS: From 11.0' ft. to 4.0' ft. From 4.0' ft. to 4.0' ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 1 ft. From 1 ft. to 1 ft. From 1 ft. to 1 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet? 150'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	CONCRETE			
1.0	5.0	Gr. Br. Silty Clay			
5.0	11.0	Highly Weathered Limestone			
	11.0	Limestone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/8/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 602 This Water Well Record was completed on (mo/day/yr) 5/27/97 under the business name of Hydro-LOGIC, Inc. by (signature) Septim P. Carter					