		,	WATE	R WELL REC	ORD F	orm WWC	-5 KS	A 82a-1	1212 ID	No.	SV	-3			
1 LOCATI	ON OF W	ATER WELL:		Fraction					Number		wnship	Number		Range Nun	nber
County: 1	Num	lotte.		NE 1/4	SE	14 NU	U 1/4		3	Т		s	F	24	E V
Distance a	nd directio	n from neares	st town	or city street	address of	well if loc	ated with	in city?			•				
N1,2	00 Fe	et Nor	HL .	of Spe	sker k	كمحط									
2 WATER	WELL OV	VNER: 14-	rero	s Chemic	ماد تلد										
RR#. St. A				Speaker						В	oard of A	aricultur	e, Divisi	ion of Water	Resources
City, State				s City.	Kansa	, La	106					Numbe			
			H 4	DEPTH OF	COMPLETE	D WELL.	20		ft. ELEV	ATION:	765.4	7			
_	IN SECTIO			epth(s) Ground											
	Ņ			ELL'S STATIC											
 	}	1													
	_ NW	Pump test data: Well water was												anm.	
	X	Bore Hole Diameter. 10,5 in. to 20ft., and in. to											ff		
§ w	E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well														
- '	-			1 Domestic	3 Feedl		Oil field			9 Dewat	_			(Specify be	TOW
	- sw l	sE		2 Irrigation	4 Indus							50.1	Veo	or Extr	-etion
	ji	1	١										•	•	
<u> </u>	1	ı		as a chemical/l	oacteriologica	al sample s	ubmitted to	o Depart							
ELTYPE C	S BLANK	CASING USE		itted	5 Wrought	iron	0.0		Wate	er Well D	isinfecte	d? Yes	N	N Clamp	lo N/A
_		3 RMP			6 Asbestos			oncrete			ASING J				
1 Stee	_	4 ABS	(SH)						ecify belo	•				.	
				9	7 Fiberglas							'	nreaded	d 🏋	• • • • • • • • •
Blank cas	ing diamet	er 	• • • • •	in. to 2	Υπ.,	, Dia		in. to			ft., Dia .	• • • • • •	ir	n. to	
Casing he	eight above	land surface.	· · · · · ·	: . -7] i	n., weight .				lbs	./ft. Wall	thickness	s or gaug	e No	Zhegwie	<u> 40 </u>
									10 As	sbestos-c	ement		į		
1 Stee		3 Stainl					8 RMP (SR) 9 ABS			11 Other (specify)					
2 Bras		4 Galva			6 Concrete		_						• •	•	
	OH PERF	ORATION OF	Iot	5 Gauzed wrapped 6 Wire wrapped					8 Saw cut 11 None (open hole) 9 Drilled holes						
	vered shut			ounched		7 Toro		•							ft
				From	10				ft From						
CONLLIN	≺~~A	TILD INTER	VALO.	From		ft. to			. ft., From	m			ft. to		ft
	GRAVEL	PACK INTERV	VALS:	From	.8	ft. to	20	?	. ft., Fron	m			ft. to		ft.
				From		ft. to	<i>.</i>		. ft., Fros	m			ft. to		ft.
6 GROUT	MATERIA	AL: Nea	t ceme	ent	2 Cement	grout	3 Be	entonite	4	Other					
Grout Inte	ervals: Fr		_	ft. to 8	ft.,	- From		ft. to.							
				contamination						stock per				doned water	
1 Sept	tic tank	4 La	teral li				,	•				1	5 Oil we		
	er lines		ess po					12 Fertilizer storage				16 Other (specify below)			
		er lines 6 Se			• •					cticide sto	•			Storme	
	•	East or		West						any feet?	•	5 8			(ASE)
FROM	ТО			HOLOGIC LO	ıG		FRO	м	TO	,		UGGING		RVALS	رمدال
		+				110	\		-					TTALO	
0	0.5	Dense,)	Gray S	4 - 18 -	•	<u>u)</u>								
0.5'	3.5'	1	7~	- 1	CAYLLIVE		-								
3.51	13.5	LIGHT	משפו		e graine	·									
	111 -1	+			ad CAIM			-							
13.5	14.5			4 SILT				-							
14.5'	20.0	Light	. '	kery F		•	-	+							
			<u></u>	ty sand	CAlley	um)	-								
		<u> </u>											-		
				CERTIFICAT											
				- 0.1											ef. Kansas
Water Well	Contracto	r's Licence No	o 2	53 1	Thi	s Water W	ell Recor	d was c	ompleted	on (mo/d	ز (lay/yr	5>	18.7	رز دراو	<i>[</i>
under the b	ousiness na	ame of Geo	steel	mical 3	~~\1\ ~\$ /	K. T.			by (s	ignature)	Mi	W /		11/4	フー
INSTRUCT	IONS: Use tvo			EASE PRESS FIRE				, underline	or circle the	correct answ	ers. Send to	p three coni	es K Kans	as Department of	Health and
				0-0001. Telephone											