		WAT	ER WELL RECORD	Form WWC-5	KSA 82a		
LOCATION OF WA		Fraction		Sect	tion Number	· · ·	Range Number
County: Wyano	otte	NW 1		W 1/4	13	T // S	R 24 (EM
Distance and direction	from nearest to	wn or city street	address of well if locat	ed within city?	0 0 1	01	
650'E 0	f 55 5	+ Speaker	Rd and 11	5 1 0F	Speak	4 Kd	
WATER WELL OV	VNER: TH A	grich ture	* Nutrition				
R#, St. Address, Bo	ox#:/5 ⁻ 37	13 W95	~			Board of Agriculture	, Division of Water Resource
Tibe Chaha 71D Cada		A E \ (a/a	1.17			Application Number	
LOCATE WELL'S	LOCATION WITH	DEPTH OF	COMPLETED WELL.	۶ <u> </u>	. ft. ELEVA	TION: 762.30T.	0. 4
AN X IN SECTIO	N DOX:	WELL'S STATI	C WATER LEVEL . */.	ネ・3.ゲ ft. be	elow land sur	face measured on mo/day/y	3
		Est. Yield	gpm: Well wa	iter was	ft. a	fter hours	pumping gpm
• i		Bore Hole Diar	meter 🎖in. t	o2 <i>.D</i>	ft.,	and 2// 4	in. to 83 .5tt
w X i	, i	WELL WATER	TO BE USED AS:	5 Public wate	r supply	8 Air conditioning 1	1 Injection well
- 1		1 Domesti			er supply	9 Dewatering 1:	2 Other (Specify below)
3	;	2 Irrigation				10 Monitoring well . M. H.	
i		Was a chemica	I/bacteriological sample	submitted to De	epartment? Y	es; If ye	es, mo/day/yr sample was sul
	\$	mitted			Wa	ter Well Disinfected? Yes	No ×
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINTS: GIL	ied Clamped
1_Steel	3 RMP (S	SR)	6 Asbestos-Cemen	t 9 Other	(specify belov	v) We	lded
(2)°VC	4 ABS		, 7 Fiberglass			Thi	readed 🗸
Blank casing diamete	r ./	in. to	7 ft., Dia				. in. to ft
Sasing height above	land surface. 🗔	0.58fr	in., weight	1.5	fbs./	ft. Wall thickness or gauge	No. Seh. 4.D.
TYPE OF SCREEN (OR PERFORATION	ON MATERIAL:		ØPV(C	10 Asbestos-cer	ment
1 Steel	3 Stainles	ss steel	5 Fiberglass	8 RM	P (SR)	11 Other (specif	ý)
2 Brass	4 Galvani	ized steel	6 Concrete tile	9 AB	3	12 None used (open hole)
CREEN OR PERFO	RATION OPENI	NGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Continuous sl	ot 🕉	Mill slot	6 Wire	e wrapped		9 Drilled holes	
2 Louvered shu	tter 4 k	Key punched	7 Toro	ch cut		10 Other (specify)	
SCREEN-PERFORAT	ED INTERVALS	: From	3.4.4	93,4	ft., Fro	m ft.	
GRAVEL PA	ACK INTERVALS	s: From 43	2 ft. to 2	83.5 (Na+S	∽. ∮)ft., Fro	m ft.	. toft . toft
		From	ft. to		ft., Fro	m , ft.	to , ft
GROUT MATERIA	L: 1 Neat	cement	2 Cement grout	3 Bento	nite 4	Other Coment - ben	איחש
Grout Intervals: Fro	om.4.2	.ft. to . 2.	ft., From .2	ft.	OB Cond	rik ft., From	ft. to
What is the nearest s	ource of possible	e contamination:			10 Lives	tock pens 14	Abandoned water well
1 Septic tank	4 Late	eral lines	7 Pit privy		11 Fuel	storage 15	Oil well/Gas well
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)		
3 Watertight se	wer lines 6 See	page pit	9 Feedyard		13 Insec		plume
Direction from well?	Fast		·		How ma	ny feet? 750	,
FROM TO		LITHOLOGIC	CLOG	FROM	ТО		INTERVALS
0 6	low pla	she CLAY	, OL, (F;11)				
6 41		1. SAND	SM, CATLUNI	ian			
41 83.5	F-E SA	ND, 5P,	(Alluvim)	7			
		,	·				
	 						
	 						
	1						- de la constitución de la const
CONTRACTOR'S	OR LANDOWNE	ER'S CERTIFICA	TION: This water well	was (1) constru	cted, (2) reco	onstructed, or (3) plugged u	nder my jurisdiction and wa
completed on (mo/da	y/year) . 1 ! 7.	-14.0.4					knowledge and belief. Kansa
				Well Record wa		on (mo/day/rr) 1.7.7.3	
under the business n	ame of / up <	Corone	+1200		by (signa	ture) Mand Co.	(Weballs
		<u> </u>	- 7 0 + 4			1 - 1 - 1 - 1	THE
INSTRUCTIONS: Use	typewriter or ball point	t pen. PLEASE PRESS	FIRMLY and PRINT clearly. I	Please fill in blanks, u	inderline or circle	the correct answers. Send top threw WNER and retain one for your reco	ee copies to Kansas Department