

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NW 1/4 Section Number 13 Township Number T 11N Range Number R 24E
 County: Wyandotte

Distance and direction from nearest town or city street address of well (if located within city):

South of Kansas River, North of Levee, West of Harcross Chem, Kansas City KS

2 WATER WELL OWNER: T H Agriculture & Nutrition

RR#, St. Address, Box # : 15313 West 95th Street

City, State, ZIP Code : Lenexa KS 66219

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 73 ft. ELEVATION:

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered 1 3.4 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 34 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Recovery

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF RANK CASING USED:

- 1 Steel
2 PVC
3 RMP (SR)
4 ABS

- 5 Wrought Iron
6 Asbestos-Cement
7 Fiberglass

- 8 Concrete tile
9 Other (specify below)

CASING JOINTS: Glued Clamped Welded Threaded

Blank casing diameter 8.10 in. to 60.5 ft. Dia 10 in. to 70 1/2 - 71 1/2 Dia in. to ft.

Casing height above land surface 36 in. weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel
2 Brass
3 Stainless Steel
4 Galvanized Steel

- 5 Fiberglass
6 Concrete tile

- 7 PVC
8 RMP (SR)
9 ABS

- 10 Asbestos-Cement
11 Other (Specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot
2 Louvered shutter
3 Mill slot
4 Key punched

- 5 Gauzed wrapped
6 Wire wrapped
7 Torch cut

- 8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 60.5 ft. to 70.5 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 39 ft. to 73 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout intervals: From 5.5 ft. to 34 ft. From 34 ft. to 39 ft. From ft. to ft.

What is the nearest source of possible contamination:

- 1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit
7 Pit privy
8 Sewage lagoon
9 Feedyard

- 10 Livestock pens
11 Fuel storage
12 Fertilizer storage
13 Insecticide storage
14 Abandoned water well
15 Oil well/Gas well
16 Other (specify below)
Industrial Site

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	24	Lt brown sandy silt			
24	43	Lt brown silty fine sand w/ clay seams			
43	71	Lt brown coarse sand w/ gravel and clay seams			
71	73	Lt brown limestone			
					RECEIVED
					AUG 30 2004
					BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/28/04 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's Licence No 570 This Water Well Record was completed on (mo/day/yr) 2/25/04 under the business name of AQUADRILL INC. by (signature) Steve Edberg

INSTRUCTIONS: Use typewriter or ballpoint pen. PLEASE PRESS HARDLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-6622. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each reconstructed well.