V	WATER WELL RECO	ORD Form WWC-5	KSA 82a-1212				
1 LOCATION OF WATER WELL:	Fraction		Section Nu	ımber Townshi	p Number	Range Number	er
county: Wyandotte	NE 14	NE 14 SE	14 5	т (l s	R 24	(E)W
Distance and direction from neares				12 -			
1850 Freema	n Avenu	e. Kansas	Citic	KS			
2 WATER WELL OWNER : C		vian Manor		4-	MWY		
RR#, St. Address, Box # : 765	n Freeman	Ave		Board o	1-000	Division of Water Re	esources
	1505 City		2_		ion Number:		
3 LOCATE WELL'S LOCATION WIT	H 4 DEPTH OF C	OMPLETED WELL	5 ft. I	ELEVATION:			
AN "X" IN SECTION BOX:		vater Encountered 1.					
- P	WELL'S STATIC V	VATER LEVEL . 4. 80	. ft. below land	surface measured on	mo/day/yr		
↑		test data: Well water w					1
NW NE		gpm: Well water w					
		erin. to					
W W	I	D BE USED AS: 5 Pub				njection well	
- X	1 Domestic	3 Feedlot 6 Oil	field water supply	9 Dewatering	12 (other (Specify below	w)
swse	2 Irrigation	4 Industrial 7 Don	nestic (lawn & gar	den 10 Monitoring w	ell		
	\A/a= = = = = = = = = = = = = = = = = = =	atariala sisal a santa a desa	ittaal ta Danastusan	10 Van Na	. 16		
<u> </u>	mitted	cteriological sample subm	itted to Departmer	Water Well Disinfed		no/day/yrs sample i No	was sub-
5 TYPE OF BLANK CASING USE		Wrought iron	8 Concrete tile			ed Clamped.	
1 Steel 3 RMP		Asbestos-Cement	9 Other (specifi			ded	
2PVC 4 ABS	, ,	Fiberglass				aded.	
Blank casing diameter		0				, , , , , , , , , , , , , , , , , , , ,	
Casing height above land surface.							
		, weight	(7)PVC				
TYPE OF SCREEN OR PERFOR 1 Steel 3 Stainl		Fiberglass	8 RMP (SR)		Asbestos-cen		
1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile			9 ABS		11 Other (specify)		
SCREEN OR PERFORATION QU		5 Gauzed		8 Saw cut		11 None (open h	(مام)
	Mill slot	6 Wire wra	1 1	9 Drilled ho	les	11 None (open ii	loie)
	Key punched	7 Torch c					ft.
SCREEN-PERFORATED INTERV	ALS: From	ft. to	ft	., From	ft. :	to	ft.
	From , .	ft. to	, <u> f</u> t	., From	ft. [.]	to	ft.
GRAVEL PACK INTER\	/ALS: From	f ft. to		., From	ft. i	to	ft.
	From	ft. to	~			a constant	1
			3 Bentonite	4 Other COM	ent. O	.2	
Grout Intervals: From	ft. to	ft., From	ft. to	ft., Fron	۱	ft. to	ft.
What is the nearest source of pos	ssible contamination:		-	Livestock pens		bandoned water we	ell
1 Septic tank 4 La	1 Septic tank 4 Lateral lines 7 Pit privy		11 Fuel storage former 15 Oil well/Gas well				
2 Sewer lines 5 Cess pool 8 Sewage		8 Sewage lag	lagoon 12 Fertilizer storage 16 Other (specify below)				
3 Watertight sewer lines 6 Se	epage pit	9 Feedyard	13	Insecticide storage			
Direction from well?			Ho	ow many feet?			
FROM TO	LITHOLOGIC LOC	à	FROM TO		PLUGGING II	NTERVALS	
O I Toos	1100		•	T=1		1-111	
4 le Clay	D. Word.	noist			MUSUM	junt vva	ive-
J Sha'	e liant 1	orown		1	Jan Jan	T 1	
	91.0			K	NX T	1 Tay 40	
				997A	.0		
					R	ECEIVED	
					SE	P 2 2 2004	
				1			=
	$\nu =$				BURE	AU OF WATER	0
						1071	:5
				100			
			2				
7 CONTRACTOR'S OR LANDOW	NER'S CERTIFICATION	ON: This water well was	(1) constructed.	(2) reconstructed, or	(3) plugged ur	der my jurisdiction	and was
completed on (mo/day/year)8 !!	9104	7		s record is true to the			
Water Well Contractor's Licence Nk				oleted on (mo/day/w	(6 4 4 1	94	
under the business name of	Control of the Contro				119	Jr	
	dalmi	Tac		by (signature)	1/7	000	I
INSTRUCTIONS: Use typewriter or ball point	drologic	Inc		by (signature)	7	- O. Duly	~