


1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Jackson WYANDOTTE SE 1/4 NW 1/4 NW 1/4		13		T 11 S		R 24 E/W	
Distance and direction from nearest town or city street address of well if located within city? 5200 Spenser Rd. Kansas City, KS in the back of the facility							
2 WATER WELL OWNER: T H Agriculture & Nutrition							
RR#, St. Address, Box # : 15313 West 95th Street				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Lenexa, KS 66219				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 33 ft. ELEVATION: -					
		Depth(s) Groundwater Encountered 1 Not encountered ft. 2 - ft. 3 - ft. WELL'S STATIC WATER LEVEL - ft. below land surface measured on mo/day/yr - Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Vapor point					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 1 in. to 2.3 ft., Dia - in. to - ft., Dia - in. to - ft. Casing height above land surface Flushmount in., weight Sch. 40 lbs./ft. Wall thickness or gauge No. - TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 23 ft. to 33 ft., From - ft. to - ft. GRAVEL PACK INTERVALS: From 2.0 ft. to 33 ft., From - ft. to - ft. From - ft. to - ft., From - ft. to - ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 2 ft. to 20 ft., From - ft. to - ft., From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 33 Alluvial sands							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/2/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 710 This Water Well Record was completed on (mo/day/yr) 8/8/05 under the business name of Below Ground Surface, Inc. by (signature) [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							