			Form WWC-5	Divi	sion of W	ater Resources:	App. No.		
1 LOCATION	OF WA	TER WELL:	Fraction	S	ection N	umber Tow	nship Number	Range Number	
County: Wyandotte SE ½ SE ½ SW ½ 15 T 11 S R 24 E  Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)									
located within city? 6700 Kaw Dr.  Latitude: N 39.08917°									
Kansas City, KS 66111 Longitude: W 94.73422°									
2 WATER WELL OWNER: Carole Smith Elevation: RIM: 777.55 TOC: 777.26									
					Datum: above mean sea level Data Collection Method: legal survey				
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 52 ft.									
LOCATON MW5									
WITH AN "	X" IN	Depth(s) Groun	dwater Encountered 1				ft. 3	ft.	
SECTION B		WELL'S STAT	TIC WATER LEVEL	46.95 ft.	below la	nd surface me	asured on mo/d	lay/yr 4/2/08	
N Pump test data: Well water was ft. after hours pumping gpm									
Est. Yield gpm: Well water was ft. after hours pumping gpm									
NW—NE— WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
W   1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
W E 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well									
-sw-se-									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs									
S Sample was submitted Water Well Disinfected? Yes No X  5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped									
5 TYPE OF C	ASING	USED: 5	Wrought Iron	8 Concret	e tile	CASING JO	OINTS: Glued	Clamped	
1 Steel	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded								
(2) PVC 4 ABS 7 Fiberglass Threaded X									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 32 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.29 ft., Weight lbs./ft. Wall thickness or gauge No.									
Casing height below land surface 0.29 ft., Weight lbs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete file 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)									
ISCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 32 ft. to 52 ft. From ft. to ft.									
SCREEN-PERFORATED INTERVALS: From 32 ft. to 52 ft. From ft. to ft.									
From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 31 ft. to 52 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 31 ft. to 52 ft. From ft. to ft.									
į.			From	ft. to		ft. From	ft. t	o ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other concrete, 0-2 feet									
Grout Intervals From 2 ft. to 31 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify 2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)									
2 Sewer line		5 Cess pool		ll) Fuel sto				below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard  Direction from well? Southeast  12 Fertilizer storage 15 Oil well/ gas well  How many feet? ~75 feet									
							LICCINIC INT	CDMALC	
FROM TO	Asp		LOGIC LOG	FROM 33	TO 35		UGGING INTI	ray, saturated, no odor	
0 1			gravel, dark brown, poor	38	40	+		ately sorted, slightly	
1 - 3 - 1 - 3		very, moist, no odor	graver, dance of own, poor	1		moist, no odor	m graniou, modera	sery sortes, sngmy	
8 10		with clay, brown, mo	ist, no odor	43	45	Sand, tan, coarse	grained, moderate	ly sorted, slightly	
13 15			ist, no odor, poor recovery			moist, no odor, g	green at ~44.75'		
18 20		with clay, brown, mo							
23 25		d with silt, trace clay, st, no odor	tan, fine to medium grained	.		<del> </del>			
28 30			tan, fine to medium grained			Flushmount waiv	ver from BOW		
	moi	st, saturated seams, n	o odor						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged									
under my jurisdiction and was completed on (mo/day/year)  Kansas Water Well Contractor's License No. 757  This Water Well Record was completed on (mo/day/year) 5/2/08									
Kansas Water Wellunder the business				iter Well Red by (signatu		completed on (in	lo/gay/year)	5/2/08	
						enartment of Haal	h and Environmen	t Bureau of Water	
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment. Bureau of Water.  Geology Section. 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for									
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.									