WATE	R WELL	RECORD	For	n WWC-	5 I	Divisio	on of Wa	ater Reso	ources; App. N	o			
1 LOCA County:	ATION OF W	WATER WELL: yandotte	Fraction SE 1/4	SE ¼	SW ¼	Sec	ction Nu 15	umber	Township I	Number S	Ran	nge Number 24 E	
County: Wyandotte SE ¼ SE ¼ SW ¼ 15 T 11 S R 24 E Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digit												in. of 4 digits	
located within city? 6700 Kaw Dr. Kansas City, KS 66111 Latitude: N 39.08919° Longitude: W 94.73386°													
2 WATER WELL OWNER: Carole Smith							Elevation: RIM: 777.34 TOC: 777.16						
2 WATER WELL OWNER: Carole Smith RR#, St. Address, Box # : 6191E. Eastman Ave. City, State, ZIP Code : Denver, CO 80222							Datum: above mean sea level						
City, State, ZIP Code : Denver, CO 80222							Data Collection Method: legal survey						
3 LUCA	5 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 51./												
i .	ATON						AW3						
WITH	I AN "X" I	N Depth(s) Grou	ndwater En	countered 1				_ ft. 2 _		ft. 3		ft.	
SECT	ION BOX	1	TIC WATE	R LEVEL	46.8	ft. b	elow lai	nd surfa	ice measured	on mo/d	iay/yr	4/2/08	
N Pump test data: Well water was ft. after hours pumping gpm													
Est. Yield gpm: Well water was ft. after hours pumping gpm													
NW NE WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well													
W I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)													
Was a shamical/heaterial agical sample submitted to Department? Very No. 1. W. 15 use ma/day/													
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs													
S Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped													
5 TYPE	OF CASI	NG USED: 5	Wrought I	ron	8 Conc	rete t	tile	CAS	ing joints	Glued	(Clamped	
1 Ste	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded												
(2) PV	/C	4 ABS 7	Fiberglass							Thread	ded	X	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded (2) PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 36.7 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.18 ft., Weight Ibs./ft. Wall thickness or gauge No.													
Casing he	ight below la	and surface 0.1	8 ft., V	Veight			lbs./	ft. Wal	ll thickness of	r gauge 1	No		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)													
2 Br	ass 4 Gal	vanized steel 6 Co	oncrete tile	8 RM (SR	2) 10	Asbe	estos-Ca	ement	12 None us	sed (one	n hole	5	
SCREEN OR PERFORATION OPENINGS ARE:													
1 Continuous slot (3) Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)													
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)													
SCREEN.	-PERFORA	TED INTERVALS	: rrom	30.7	^{II. 10} -	3	21.7	_ n. fr	om	n. t	0	π.	
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 36.7 ft. to 51.7 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 35.5 ft. to 51.7 ft. From ft. to ft. From ft. to ft. From ft. to ft.													
J. Gr	CAVELPA	LK INTERVALS:	From	33.3	ft. 10 -	3	21./	- H. FR	om 	II. U	·	II	
			FIOIII		11. 10 -			_ IL. FI		11. 1	<u> </u>	IL.	
6 GROU	UT MATE	RIAL: 1 Neat cer	nent 2 Ce	ement grout	(3 Be	ntonit	te (4	Other	concrete, 0-	2 feet			
Grout Inte	ervals F	rom 2 ft. to	35.5 ft	. From		t. to		tt.	From		ft. to	ft.	
		ource of possible co 4 Lateral li			10 1 :	+1-		12 Inco	atiaida Stana	~~	16.0		
	tic tank ver lines	5 Cess poo		rivy age lagoon (10 Live:	stora	pens		ecticide Stora andoned wate			ther (specify elow)	
											00	510W)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? SW 12 Fertilizer storage 15 Oil well/ gas well How many feet? ~65 feet													
	,		LOCICIO						DITICON	IC DITI	CDMA	I C	
FROM 0	TO	Asphalt	LOGIC LO	<u>u</u>	FRO 33	IVI	TO	Clay with	PLUGGIN h silt, some sand				
3	5	Sand (fill), coarse, brow	n moderately		33	_	33		y moist, slight p			·	
		sorted, slightly moist, ne			38	-	40		h silt, some sand				
- 8	10	Clay with rubble fill, (co		ist, asphalt,				gray, ver	y moist, slight p	etroleum o	odor		
			stone gravel, organic odor), dark olive brown		43		45	Sand, medium grained, light gray, fairly we					
13	15	Clayey silt, dark brown,							ace moisture, no	odor; coa	rse sand	i, not well	
18	20	Silt w/ clay, olive-gray,				-		sorted at	~44.5′				
23	30	Silt w/ clay, olive-gray, Silt w/ clay, olive-gray,						Flushmo	unt waiver from	BOW			
	- 50	Site we clay, on ve gray,	moist, shong	Jenoieum ouoi	1	_		- Trasilino	ant waiver from	BOW			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged													
under my jurisdiction and was completed on (mo/day/year) Kansas Water Well Contractor's License No. 757 This Water Well Record was completed on (mo/day/year) 5/2/08													
		tractor's License No.							d/on (mo/day/y	ear)	5/2/08		
under the business name of Larsen & Associates, Inc. by (signature)													
Geology Sec	INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for												
your records	s. Fee of \$5.00	for each constructed we	II. Visit us at	http://www.kdl	eks.gov/w	aterwe	ell.						