WATER WELL RE	CORD	Form W	WC-5		ter Resources App. N		
1 LOCATION OF WATER WELL:		Fraction				Range Number	
County: Wyandotte		4NW 4 SE	45E4	//		RZY DE W	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioni	ng System (GPS) is 5.15.69	(in decimal degrees)	
from nearest town or intersection: If at owner's address, check here .			Longitude: 94.42.33.42 (in decimal degrees)				
east of 57th street between Kaw Drive and I-70 ramp				Elevation:			
A WATER WELL OWNER.				Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Phillips 66 Company RR#, Street Address, Box #: 420 South Keller				Collection Method: GPS unit (Make/Model:)			
RR#, Street Address, Box #: 420 South Keller City, State, ZIP Code : Bartlesville, OK 74004			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
0.0, 5.0.0, 2	Daities	niie, OK 74004		Est. Accuracy:	<3 m, □ 3-5 m, □] 5-15 m,	
3 LOCATE WELL	4 DEPTH OF	COMDITETED WEI	45.07		A		
WITH AN "X" IN SECTION BOX:	TION BOX: Depth(s) Groundwater Encountered (1).34.08 ft. (2)						
N N	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELDgpm. Well water was							
							Dewatering Other (Specify below)
SW SE	Irrigation Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No							
s If yes, mo/day/yr sample was submitted							
water well disinfected? ☐ Yes ☑ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .1 in. to .43.07 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface .36 in., Weight							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel 77 PVC Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
☐ Lowered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut 🔽 Other (specify)							
SCREEN_PERFORATED INTERVALS: From 43.0/ ft. to45.0/ft., From							
From							
GRAVEL PACK INTERVALS: From. 41.07 ft. to .45.07 ft., From ft.							
From							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
What is the nearest source of possible contamination:							
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Distance from well							
FROM TO	LITHOLOG		FROM			UGGING INTERVALS	
TROM TO	2111020						
NA NA							
					<u> </u>	, ,	
			ļ. —				
			 				
			 				
			┼			······································	
			 				
 						-	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\big \) constructed, \(\propto \) reconstructed, or \(\propto \) plugged							
under my jurisdiction and was completed on (mo/day/year) .4/9/2014							
Kansas Water Well Contractor's License No. 604. This Water Well Record was completed on (mo/day/year)							
under the business name	of Environme	ntal Priority Service, I	П С .	by (signature)	ake and check the	t anguage Cand one come to	
INSTRUCTIONS: Use typ	of Health and Environ	ment Rureau of Water Geo	logy Section 1	000 SW Jackson St., S	uite 420. Topeka, Kans	as 66612-1367.	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
		http://www.kdheks.go	v/waterwell/inde	x html			