


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		1/4 NE 1/4 NW 1/4	4	T 11 S	R 24 (EW)
Distance and direction from nearest town or city street address of well if located within city? 7705 Parallel Avenue, Kansas City, Kansas					
2 WATER WELL OWNER: Amoco Oil Company					
RR#, St. Address, Box # : 8700 Indian Creek Parkway			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Overland Park, Kansas			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17.0 ft. ELEVATION:			
<div style="text-align: center;"></div>		Depth(s) Groundwater Encountered 1. 11.7 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.0 ft. below land surface measured on mo/day/yr 3-2-90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter: 7 in. to 19.5 ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		7 Fiberglass		Welded Threaded X	
Blank casing diameter 2 in. to 7.5 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface -40 ft. weight lbs./ft. Wall thickness or gauge No. SCH. 40 p.v.c.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		7 PVC 10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 7.5 ft. to 16.0 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 6.5 ft. to 17.0 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 4.5 ft. From 4.5 ft. to 6.5 ft. From 17.0 ft. to 19.5 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? N.E.		How many feet? 10'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0'	Fill, 3" asphalt over 9" fine to coarse gravel, boulder at 1".			
1.0'	6.5'	Lean clay, brown wigh gray mottles, moist, very soft to soft (loess).			
6.5'	9.4'	Lean to fat clay, brown, yellow, red, gray mottled, with sand, moist, firm to very firm (glacial till) increasing sand content with pebbles.			
9.4'	14.7'	Limestone, with shale stringers, extremely weathered 9.4-11.5', wet, hydrocarbon odor, becoming unweathered.			
14.7'	19.5'	Shale, olive green, dry, becoming reddish-orange, becoming maroon and gray mottled.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/26/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3-7-90 under the business name of Terracon Consultants by (signature) <i>W. G. Semley</i>					