

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County <u>WYANDOTTE</u>		<u>SE 1/4 NW 1/4 NW 1/4</u>	<u>11</u>	<u>T 11 S</u>	<u>R 24 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>746 NORTH 63RD STREET KC, KS</u>					
2 WATER WELL OWNER: <u>MARK BISHOP</u>					
RR#, St. Address, Box # : <u>746 N 63rd ST KANSAS CITY</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>61</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>DRY</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>DRY</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>DRY</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter... <u>10</u> in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass	<u>DRY HOLE</u>	Threaded
Blank casing diameter in. to ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From ft. to ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	<u>CREEK</u>
Direction from well? <u>500' WEST</u>		How many feet? <u>500</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	SURFACE			<u>A CUSTOMER ADVISED US HE WOULD PLUG WELL</u>
2	22	CLAY (RED)			
22	23	LIME FLOATERS			
23	26	BLUE MUD			
26	29	CLAY (YELLOW)			
29	37	COARSE SAND FINE GRAVEL			
37	38	GRAVEL (SMALL)			
38	39	LINESTONE GRAVEL			
40	41	LIME			
41	48	SHALE			
48	51	LIME			<u>well #3</u>
51	53	SHALE			
53	54	LIME			
54	61	SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4/20/89</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>240</u> This Water Well Record was completed on (mo/day/yr) <u>5/2/89</u>					
under the business name of <u>FE. YOUNG DALLING CO</u> by (signature) <u>Red Young</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4