

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: wyandotte		NE 1/4 SW 1/4 SE 1/4	13	T 11 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city? 5000 Kansas Avenue - Kansas City, Kansas 66106					
2 WATER WELL OWNER: Associated Wholesale Grocers, Inc.					
RR#, St. Address, Box # : 5000 Kansas Avenue			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Kansas City, Kansas 66106			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 49.3 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 33.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 35.6 ft. below land surface measured on mo/day/yr 8/16/85 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6-1/4 in. to 52.5 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Monitoring Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter 2 in. to 23.9 ft., Dia		7 Fiberglass	Threaded X		
Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Sched. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 23.9 ft. to 49.3 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 3.0 ft. to 49.3 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other Bentonite/cement grout	
Grout Intervals: From 0.0 ft. to 3.0 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? Southwest				How many feet? 180'	
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0.0	0.6	Concrete			
0.6	1.0	Sand & gravel			
1.0	3.0	Sandy silt			
3.0	10.5	Sandy silty clay			
10.5	31.0	Silty fine sand			
31.0	52.5	Fine sand			
52.5	Total	Depth			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/29/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 8/15/85 under the business name of Layne-Western Company, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					