


1 LOCATION OF WATER WELL: County: Wyandotte	Fraction SW 1/4 SE 1/4 NW 1/4	Section Number 13	Township Number T 11 S	Range Number R 24 EW
--	----------------------------------	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

1400 ft E of 55th & Speaker Road, Kansas City, KS

2 WATER WELL OWNER: Thompson-Hayward Chemical Company RR#, St. Address, Box #: 5200 Speaker Road City, State, ZIP Code: Kansas City, Kansas 66106	Board of Agriculture, Division of Water Resources Application Number: NA
---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 86 ft. ELEVATION: 762 Depth(s) Groundwater Encountered 1. 37 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 37 ft. below land surface measured on mo/day/yr 3-28-85 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6-3/4 in. to 55 ft. and 3.5 in. to 87 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
--	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 2 in. to 76 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 24 in. weight lbs./ft. Wall thickness or gauge No. Sched. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 76 ft. to 86 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 87 ft. to 35 ft. From ft. to ft.
--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement-Bentonite Grout Grout Intervals: From 30 ft. to 38 ft. From 0 ft. to 30 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Chemical Plant Direction from well? How many feet?
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	Silt, Sandy, brown			
1	2.5	Sand, Silty, fine, brown			
2.5	8.5	Silt, low plastic, brown			
8.5	63.0	Sand, poorly graded, tan-gray & brown			
63.0	66.0	Gravel, poorly graded			
66.0	68.0	Sand, poorly graded, tan			
68.0	69.0	Boulder			
69.0	86.0	Sand, poorly graded, tan			
86.0	87.0	Shale, Silty/Sandy, hard, medium gray			
	87.0	Bottom of boring			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) March 29, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day/yr) April 10, 1985 under the business name of Woodward-Clyde Consultants by (signature) Richard L. Mohr INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.
--