			WA-	ren wei	L RECOR	אט	Form WW	VC-5 K	SA 82a	a-1212		RW-1				
1 LOCATION OF WATER WELL: Fraction								Section N		•	hip Nur	nber	R	ange Nu	mber	
County:	Wyandot			1/4 SV	/4	NW	1/4	13		Т		S	R	24	<b>D</b> W	
		from nearest to						ity?							_	
5420	Speaker	Road (app	proximately	y 100'	north	of	road)									
2 WATE	R WELL OW	/NER: Ashla	and Chemic	al Co.	•											
RR#, St.	Address, Bo	× # : 5420	Speaker R	oad						Boar	d of Ag	riculture,	Division	of Water	Resources	
		: Kansa										Number:				
LOCAT	E WELL'S L	OCATION WITH	4 DEPTH OF	COMPL	ETED WE	LL	60	ft.	ELEVA	ATION:						
' AN "X"	IN SECTION	N BOX:	Depth(s) Grou	ndwater	Encountere	ed 1.			ft. :	2		ft.	3		ft.	
τ Γ	ı		WELL'S STAT													
I	1	J.	1							after						
] [	NW	NE	Est. Yield													
<u>.</u>	ĸ i	i   .	Bore Hole Dia													
A S	ı	ı	WELL WATER					water supp		8 Air condit			Injection			
7	1		1 Domest	ic	3 Feedlot				-	9 Dewaterir	ng J	(12	Other (S	Specify b	elow)	
1 1	SW	SE	2 Irrigation	n	4 Industria					10 Monitorin						
1 1	ì		Was a chemica	al/bacteri	ological sa											
1 -			mitted		_	·		•		ater Well Disi			-	No		
5 TYPE	OF BLANK (	CASING USED:		5 Wr	ought iron		8 Cc	oncrete tile						. Clampe	ed	
1 St	eel	3 RMP (S	iR)	6 As	bestos-Ce	ment	9 Ot	ther (specif	y belov					-		
(2)P\	/C	4 ABS 4''		7 Fit	erglass				·	·		Thre	aded			
Blank casi	ing diameter	<b>4</b> ''	.in. to	<i></i> .	ft., Dia		ir	n. to		ft., Dia .			in. to .		ft.	
		and surface														
		R PERFORATIO			•			PVC				stos-cem				
1 St	eel	3 Stainles	s steel	5 Fit	erglass		8 RMP (SR)			1	1 Other	(specify	)			
2 Brass 4 Galvanized steel					6 Concrete tile			ABS	•	12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:					5 Gauzed wra			ed	8 Saw cut	· • • • • • • • • • • • • • • • • • • •			n hole)			
							vrapped	rapped 9 Drilled h			oles				,	
2 Lo	uvered shutt	ter 4 K	(ey punched		7	Torch	cut			10 Other (s	specify)					
SCREEN-	PERFORATI	ED INTERVALS:	From	<i></i>	ft.	to			ft., Fro	m		ft.	to			
			From		ft.	to			ft., Fro	m , .		ft.	to			
(	GRAVEL PA	CK INTERVALS								m ,						
			From			to			ft., Fro							
6 GROU	T MATERIAL		cement		nent grout			entonite		Other						
Grout Inte	rvals: Froi	m <b>3</b>	.ft. to <b>6.0</b>	<b>⊘</b> f	t., From .	6		ft. to:	3 G	🔊 ft., Fro	om		ft. to	,		
What is th	e nearest so	ource of possible	contamination:					10	Lives	stock pens		14 /	Abandone	d water	well	
1 Septic tank 4 Lateral lines					7 Pit privy			11 Fuel			storage			15 Oil well/Gas well		
2 Sewer lines 5 Cess pool					8 Sewage lago						izer storage 16			Other (specify below)		
3 W	atertight sew	er lines 6 Seep	page pit		9 Feedy	ard				ticide storage	э.					
Direction 1	from well?									ny feet?						
FROM	ТО		LITHOLOGI	C LOG			FROM	и тс	)		PLU	GGING	INTERVA	LS		
0	3	Holeplug	& benton:	ite												
3	60	Portland	cement gr	rout w	/bento	nite	<u>.</u>									
		(Screens	& casing v	were r	ulled)	1										
,																
									- T							
											*	CONTROL OF THE PARTY OF THE PAR				
	1															
			PA-12-12-12-12-12-12-12-12-12-12-12-12-12-				1		1							
7 000-		DR LANDOWNE	D'S CERTIEICA	TION!	nie water :	سد الميد	e (1) con	etruoted /	2) reco	netructed or	(A) al	aged un	der mili	risdiction	n and wee	
		year) $1$			nis water v					ord is true to t						
		s License No $10$								on (mo/dey/y					or nanoas	
	business na		e-Western			TIOL AA	Si HECOIC		signa)	4/1.	`` <i>\\</i> *1		TIA. 1			
		ypewriter or ball point				parly Dia	ase fill in his				were Son	d top thr	WWW.	aneae Do-	artment	
of Heal	th and Environm	ypewriter or ball point lent, Bureau of Water	, Topeka, Kansas 66	620-7320. 1	Telephone: 91	3-296-55	45. Send on	e to WATER	WELL O	WNER and retain	n one for	your recerd	is.	штэаз пер	ai iii lefil	