			WAT	ER WELL RECOR	ID Form W	WC-5	KSA 82	2a-1212	MW-11B			
1 LOCATI	ON OF WAT	ER WELL:	Fraction			Section	Numbe	1	ip Number	Ra	nge Nur	nber
	Wyandott			4 SE 1/4	NW 1/4	1	.3	Т	11 s	R	24	E/XX
				address of well if I		city?						
520	0 Speake			Plant Entra	ance							
2 WATE	R WELL OW		ors Chemica									
RR#, St.	Address, Box		Speaker Ro					Board	of Agriculture	e, Division o	of Water	Resources
	e, ZIP Code		is City, KS						ation Number			
LOCAT	E WELL'S LO	OCATION WITH	4 DEPTH OF	COMPLETED WE	LL52	<u>.</u> f	t. ELEV	ATION:				
- AN "X"	IN SECTION	N BOX:	Depth(s) Groun	dwater Encountere	_{ed 1} 3	9	ft.	2	<i></i> ft.	3		ft.
ī [!	1	WELL'S STATE	C WATER LEVEL	39	. ft. belov	v land s	urface measure	ed on mo/day/	_{yr} 10,	1/90	
	NW	- NE -		np test data: Wel								
] [\\\\ X	- 196	Est. Yield	gpm: Wel	ll water was		ft.	after	hours	numping		anm
	<u>i</u>		Bore Hole Dian	neter8i	in. to	52	ft.,	and		in. to		
A Pie	1	, ,		TO BE USED AS:		c water su		8 Air condition		1 Injection		
7	csv.	1	1 Domestic	3 Feedlot	6 Oil fie	eld water s	supply	9 Dewatering	-	2 Other (S	pecify be	elow)
	SW	SE	2 Irrigation	4 Industria	al 7 Lawn	and gard		10 Monitoring	_			
1	ij	i	Was a chemica	l/bacteriological sai								
<u> </u>	S		mitted					ater Well Disin			No	
5 TYPE	OF BLANK C	ASING USED:		5 Wrought iron	8 (Concrete t			JOINTS: GIL			d <i></i>
1_St		3 RMP (S	R)	6 Asbestos-Cer		Other (spe	ecify belo			elded	•	
(2)P\	/C	4 ABS		7 Fiberglass					Th	readed	X	
Blank casi	ing diameter	. 2	in. to 22	ft., Dia		in. to		ft., Dia .		. in. to		ft.
			24									
TYPE OF	SCREEN OF	R PERFORATIO	N MATERIAL:	_		7 PVC			Asbestos-cei			
1 St	eel	3 Stainles:	s steel	5 Fiberglass	`	8 RMP (9	SR)	11	Other (specif	ίν)		
2 Brass 4 Galvanized steel 6 Cond						9 ABS	•		None used (• •		
SCREEN OR PERFORATION OPENINGS ARE:					Gauzed wrapp	Gauzed wrapped			`	11 Non	e (open	hole)
1 Continuous slot 3 Mill slot 6 Wire v						pped 9 Drilled holes			oles			,
2 Lo	uvered shutte	er 4K	ey punched		Torch cut			10 Other (sp	pecify)		<i>.</i>	
SCREEN-	PERFORATE	D INTERVALS:	From	22 ft.	to	52	ft., Fre	om , , ,	ft	. to		ft.
				ft.								
(GRAVEL PAG	CK INTERVALS:	From	18 _{ft.}	to	52	ft., Fr	om	ft	to		ft.
			From	ft,	to		ft., Fr	om	ft	to		ft.
GROUT	T MATERIAL			2)Cement grout		Bentonite		Other				
Grout Inte	rvals: Fron	n 0	. ft. to . 15	ft., From .	. 15	ft. to	. 17 .	ft., Fro	m <i>.</i>	ft. to		ft.
What is th	e nearest so	urce of possible	contamination:		(ben	conite	ने0 Live	stock pens	14	Abandone	d water v	vell
1 Se	eptic tank	4 Later	ral lines	7 Pit priv				l storage	15	Oil well/Ga	s well	
2 Sewer lines 5 Cess po			pool	ool (8) Stewages, lago			n 12 Fertilizer sto			Other (spe	cify belo	w)
3 W	atertight sew	er lines 6 Seep		9 Feedya			13 Inse	cticide storage				
Direction 1	from well?	50' to th	e east				How m	any feet?				
FROM	то	G . 1 . c ·	LITHOLOGIC	LOG	FRO	ОМ	то		PLUGGING	INTERVA	_S	
0	3	Sandy fi										
3	10	Brown sa										
10	20		lty sand									
20	52	Brown me	dcoarse	sand	<u> </u>							
		1										
	ļ	MW-11B										
	<u> </u>											
-												
7 CONT	RACTOR'S C	B LANDOWNER	R'S CERTIFICAT	ION: This water w	vell was	onstructed	. (2) red	onstructed, or	(3) plugged u	nder neviu	risdiction	and was
	on (mo/day/	70	11 100		_			ord is true to the				
Water Wel	Contractor's	License No.		This Wa				, ,	A	/- · - I - I		
under the	business nan	ne of Layne	-Western C	o., Inc.			by (sign:	/ / M	JWI	The		
			-	FIRMLY and PRINT cle	early. Please fill in				ers. Send ton three	e copies to Ka	nsas Dena	rtment
				20-7320. Telephone: 913							ora neha	