

1 LOCATION OF WATER WELL: County: WYANDOTTE	Fraction SW 1/4 SW 1/4 NE 1/4	Section Number 13	Township Number T 11 S	Range Number R 24 EW
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?
5420 SPARK Rd Kansas City, Ks TW-1

2 WATER WELL OWNER: Asiland chemical	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 5420 SPARK Rd	Application Number:
City, State, ZIP Code : KANSAS CITY KS 66106	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: 720
	Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 39.25 ft. below land surface measured on mo/day/yr 11-11-92
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 12 in. to 42 ft., and in. to ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2</u> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 27 ft., Dia			Threaded. <input checked="" type="checkbox"/>
Casing height above land surface 0 in., weight			lbs./ft. Wall thickness or gauge No. Sch 40
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	<u>7</u> PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			10 Asbestos-cement
			11 Other (specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>3</u> Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 42 ft. to 27 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 42 ft. to 25 ft., From ft. to ft.			

6 GROUT MATERIAL:			
1 Neat cement	<u>2</u> Cement grout	<u>3</u> Bentonite	4 Other
Grout intervals: From 23 ft. to 0 ft., From 25 ft. to 23 ft., From ft. to ft.			
What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
			13 Insecticide storage
			<u>14</u> Other (specify below) CHEMICAL STORAGE
Direction from well? WEST/NORTH		How many feet? 15	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	SILT			
2	42	FINE - MED SAND			
					CASING HEIGHT
					& GROUT VARIANCE
					GRANTED BY KDHE

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . . . 11-2-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) . . . 12-2-92 under the business name of CINOWATER TECHNOLOGY by (signature) Dennis White	
--	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.