

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WYANDOTTE		NE 1/4 SE 1/4 NW 1/4	13	T 11 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city? 5200 SPEAKER RD KANSAS CITY KS					
2 WATER WELL OWNER: HARCROS CHEMICALS INC					
RR#, St. Address, Box #: 5200 SPEAKER RD Board of Agriculture, Division of Water Resources					
City, State, ZIP Code: KANSAS CITY KANSAS 64106 Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 63.5 ft. ELEVATION: 765.04			
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter in. to ft., and in. to ft.		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well			
		2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		7 Lawn and garden only 10 <u>Monitoring well</u>			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <u>X</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 4 in. to 32.5 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 32.5 ft. to 63.5 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>CEMENT BENTONITE</u>					
Grout Intervals: From 2 ft. to 63.5 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			0	2	NATIVE SOIL
			2	63.5	CEMENT/BENTONITE GROUT
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged under my jurisdiction and was</u>					
completed on (mo/day/year) 12-20-92 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 9-28-93					
under the business name of LAYNE WESTERN by (signature) <u>[Signature]</u>					