

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WYANDOTTE		NC 1/4 SE 1/4 NW 1/4	13	T 11 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city?					
5200 SPEAKER RD KANSAS CITY KS					
2 WATER WELL OWNER: HARCROS CHEMICALS INC					
RR#, St. Address, Box # : 5200 SPEAKER RD					
City, State, ZIP Code : KANSAS CITY KANSAS 66106					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 86 ft. ELEVATION: NA			
		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was .ft. after .hours pumping .gpm			
		Est. Yield .gpm: Well water was .ft. after .hours pumping .gpm			
		Bore Hole Diameter .in. to .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 2 in. to 25.5 ft., Dia in. to .ft., Dia in. to .ft.					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 25.5 ft. to 86 ft., From .ft. to .ft.					
From .ft. to .ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From .ft. to .ft., From .ft. to .ft.					
From .ft. to .ft., From .ft. to .ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 86 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet?					
FROM TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
				0 2 NATIVE SOIL	
				2 86 CEMENT/BENTONITE GROUT	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-20-92 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 9-28-93					
under the business name of LAYNE WESTERN by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					