			WATER	WELL RECORD	Form WWC-	5 KSA 8	2a-1212	MM-8
1 LOCATIO	ON OF WAT	ER WELL:	Fraction		Sec	ction Number		Range Number
	lyandot		NE 1/4	74	IE 1/4	⊥4	J T <sup>LL</sup> S	R 24 E/W
			•	lress of well if locate	•			
6	65 fee				of 57th	Street	and K-32.	
2 WATER	WELL OW	NER: Phill	Lips Pipe	Line Co.				
RR#, St. A	ddress, Box	# : 370 A	Adams Bldq	<b>}</b> •			Board of Agriculture,	Division of Water Resources
City State	ZIP Code	Bart]	Lesville,	OK 74004			Application Number:	
LOCATE	WELL'S LO	CATION WITH	DEPTH OF CO	MDI ETED WELL	42.4	# ELE\	752.97 (g:	round)
AN "X" I	N SECTION	BOX:	Contb(s) Groundwi	stor Engagnetored 1	29.5	II. CCC •	/ATION: 752.97 (9: . 2. ft. surface measured on mo/day/yr	tt
- C	<del> </del>	<del>- y</del> 1,	MELL'S STATIC M	VATED LEVEL 3	30.73	olow land a	urface massured on molday/vr	12/2/94
1	- i - l	- "i	VELLO STATIC V	VATER LEVEL		elow lanu s	after hours pu	maina anm
	- NW	NE	•					
1 1	1						after hours pu	
* w							, andin	
-	1 1		WELL WATER TO		5 Public water		•	Injection well
-	- SW	SE	1 Domestic	3 Feedlot		• • •	9 Dewatering 12	
	1	1	2 Irrigation	4 Industrial		-	Monitoring well	
<b>∤</b> ∟		\	Was a chemical/ba	cteriological sample	submitted to D	epartment?	YesNoX; If yes	
<del>-</del>	<u> </u>		nitted			<u>v</u>	Vater Well Disinfected? Yes	No X
5 TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS: Glue	d Clamped
1 Stee	el	3 RMP (SR)	•	6 Asbestos-Cement		(specify bel	,	led
@PV0		4 ABS		7 Fiberglass				adedX
Blank casin	g diameter	2	n. to 2.4 • .7.5	ft., Dia	in. to		ft., Dia	in. to ft.
Casing heig	ght above la	nd surface3	31.4ir	n., weight		lb:	s./ft. Wall thickness or gauge N	юSCH40
TYPE OF S	SCREEN OF	PERFORATION	MATERIAL:		<b>⊘</b> PV	'C	10 Asbestos-ceme	ent
1 Stee	el	3 Stainless	steel 5	5 Fiberglass	8 RN	IP (SR)	11 Other (specify)	
2 Bra	SS	4 Galvanize	d steel	6 Concrete tile	9 AB		12 None used (or	
SCREEN C	R PERFOR	ATION OPENING	S ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)
1 Cor	ntinuous slot	<b>3</b> МіІІ	slot		wrapped		9 Drilled holes	,
2 Lou	vered shutte	•		7 Torch	• •		10 Other (specify)	
SCREEN-P	ERFORATE	D INTERVALS:		.75 ft to	38.81	ft Fi	rom ft. t	
							rom ft. t	
G	RAVEL PAC	K INTERVALS:					rom ft. t	
_			_					to ft.
6 GROUT	MATERIAL:	1 Neat ce		Cement grout			4 Other	
_							ft., From	
								bandoned water well
What is the nearest source of possible cor 1 Septic tank 4 Lateral li			7 Pit privy			el storage 15 C		
		5 Cess p		•		<del>-</del>		of well-cas well  Other (specify below)
3 Watertight sewer lines 6 Seepag			8 Sewage lagoon 9 Feedyard		12 Fertilizer storage (6) Other (specify below) 13 Insecticide storagePetroleum.product.line			
Direction fro	_	miles o Seepa	ge bir	9 reedyard				iii. producici rriie
FROM	TO TO		LITHOLOGIC LO	)G	FROM	TO TO	any feet? PLUGGING I	NTERVALS
0	9.5	clave	y silt	<u></u>	THOW	10	, Lodding i	ITTELITALO
9.5	14.9	silt	1					
14.9	34.8	sand						
34.8	40.0		y silt					
40.0	43.0	sand	y Silc					
30.0	-3.0	Sand						
<del></del>					<u> </u>			
	-			·				
			· <del>// // // // // // // // // // // // //</del>					
CONTR	ACTOR'S O	D I ANDOWNED	C CEDTIEICATIO	V. This water well w		oted /0\	constructed, or (3) plugged unc	for my jurisdiction and was
		rear) 11/.2			_			
							cord is true to the best of my kn	Owiedge and belief. Kansas
vvater Well	Contractor's	License No		This Water W	rell Hecord wa			~ K 1.7.7
				ENGINEERI		by (sign		eres -
INSTRUC	TIONS: Use typ	ewriter or ball point pe	n. PLEASE PRESS FIRM	<u>ALY</u> and <u>PRINT</u> clearly. Ple	ease fill in blanks,	underline or cire	cle the correct ensivers. The top siree OWNER and regin one for you records	copies to Kansas Department
of Health	and Environme	nt. Bureau of water 14						