

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		1/4 NE 1/4 SE 1/4	20	T 11 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? South of Argentine Blvd., East of 26th Street, Kansas City, Kansas					
2 WATER WELL OWNER: The Atchison, Topeka, Santa Fe Railway Company				MW 95-11	
RR#, St. Address, Box #: 920 SE Quincy				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Topeka, KS 66612				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 44 ft. ELEVATION: 735.92			
		Depth(s) Groundwater Encountered 1. 13.4 ft. 2. 33.1 ft. 3. ft. WELL'S STATIC WATER LEVEL 13.4 ft. below land surface measured on mo/day/yr 4-19-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 2 in. to 29 ft., Dia. 0.70 in. to ft., Dia. Sch 40 Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From 29 ft. to 44 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 27 ft. to 44 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 23 ft. to C ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet? 1950					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		see attached	29	31	sand
			31	31.5	none
			31.5	32	sand
			32	32.5	clay
			32.5	33	sand
			33	34	none
			34	35.4	sand
			35.4	36.5	none
			36.5	37.9	sand
			37.9	44	none
0	4	none			
4	8.5	clay			
8.5	9	none			
9	12	sand			
12	13.4	clay			
13.4	14	none			
14	14.5	sand			
14.5	17.5	clay			
17.5	18.5	sand			
18.5	19	none			
19	27.2	sand			
27.2	29	none			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 7-24-95 under the business name of Lagne Inc by (signature)					