

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Wyandotte		1/4 NE 1/4 SE 1/4		20		T 11 S		R 25 EW			
Distance and direction from nearest town or city street address of well if located within city?											
South of Argentine Blvd., East of 26th Street, Kansas City, Kansas											
2 WATER WELL OWNER: The Atchison, Topeka, Santa Fee Railway Company								MW 95-1			
RR#, St. Address, Box # : 920 SE Quincy								Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Topeka, KS 66612								Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 44 ft. ELEVATION: 751.75									
		Depth(s) Groundwater Encountered 1. 34 ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL 34 ft. below land surface measured on mo/day/yr 4-4-95									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter in. to ft., and in. to ft.									
WELL WATER TO BE USED AS:											
1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    11 Injection well 2 Irrigation    4 Industrial    7 Lawn and garden only    10 Monitoring well    12 Other (Specify below)											
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No X											
5 TYPE OF BLANK CASING USED:											
1 Steel    3 RMP (SR)    5 Wrought iron    8 Concrete tile    CASING JOINTS: Glued Clamped 2 PVC    4 ABS    6 Asbestos-Cement    9 Other (specify below)    Welded 7 Fiberglass    Threaded X											
Blank casing diameter 2 in. to 29 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 0 in., weight 270 lbs./ft. Wall thickness or gauge No. Sch 40											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel    3 Stainless steel    5 Fiberglass    8 RMP (SR)    10 Asbestos-cement 2 Brass    4 Galvanized steel    6 Concrete tile    9 ABS    11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot    3 Mill slot    5 Gauzed wrapped    8 Saw cut    11 None (open hole) 2 Louvered shutter    4 Key punched    6 Wire wrapped    9 Drilled holes 7 Torch cut    10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 29 ft. to 44 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 27 ft. to 44 ft., From ft. to ft.											
6 GROUT MATERIAL:											
1 Neat cement    2 Cement grout    3 Bentonite    4 Other Grout intervals: From 25 ft. to 0 ft., From ft. to ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank    4 Lateral lines    7 Pit privy    10 Livestock pens    14 Abandoned water well 2 Sewer lines    5 Cess pool    8 Sewage lagoon    11 Fuel storage    15 Oil well/Gas well 3 Watertight sewer lines    6 Seepage pit    9 Feedyard    12 Fertilizer storage    16 Other (specify below)											
Direction from well? How many feet? 100											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
				see Attached		21		27		clay	
						22		22.5		sand	
						22.5		24.5		no recovery	
						24.5		27		sand	
						27		29.5		no recovery	
						29.5		31		sand	
						31		34		no recovery	
						34		40		sand	
						40		45		no recovery	
0		1		no recovery							
1		3		clay							
3		4		no recovery							
4		5		sand							
5		7		clay							
7		9		no recovery							
9		12		sand							
12		14		no recovery							
14		16		sand							
16		19		no recovery							
19		21		sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-4-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 7-24-95 under the business name of Layne, Inc by (signature) [Signature]											