

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		1/4 NE 1/4 SE 1/4	20	T 11 S	R 25 E
Distance and direction from nearest town or city street address of well if located within city?					
South of Argentine Blvd., East of 26th Street, Kansas City, Kansas					
2 WATER WELL OWNER:		The Atchison, Topeka, Santa Fe Railway Company			MW 95-6
RR#, St. Address, Box # :		920 SE Quincy			Board of Agriculture, Division of Water Resources
City, State, ZIP Code :		Topeka, KS 66612			Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: 750-37			
		Depth(s) Groundwater Encountered 1. 13.5 ft. 2. 27 ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 13.5 ft. below land surface measured on mo/day/yr 4-12-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter . in. to . ft., and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded Threaded X			
Blank casing diameter . in. to . ft., Dia . in. to . ft., Dia . in. to . ft.		lbs./ft. Wall thickness or gauge No. Sch 40			
Casing height above land surface . in., weight 0-10					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From . 24 ft. to . 39 ft.			
GRAVEL PACK INTERVALS:		From . 22 ft. to . 39 ft.			
6 GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From . 20 ft. to . 0 ft.		From . ft. to . ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		How many feet? 1200			
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		see attached	29.1	31.5	none
			31.5	32.5	sand
			32.5	34	none
			34	35.5	clay
			35.5	39	sand
0	1	none			
1	2.5	sand/fill			
2.5	9	clay			
9	13.5	sand			
13.5	14	none			
14	17	sand			
17	19	clay			
19	23	sand			
23	24	none			
24	26.3	sand			
26.3	29	none			
29	29.1	sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-12-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 7-24-95 under the business name of Layne dnc by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					