

1 LOCATION OF WATER WELL: County: Wyandotte		Fraction NE 1/4 NE 1/4 1/4		Section Number 19	Township Number T 11 S	Range Number R 25 EW
Distance and direction from nearest town or city street address of well if located within city? I-635 and Kansas Ave. Kansas City, KS MW-8						
2 WATER WELL OWNER: Fairbanks-Morse RR#, St. Address, Box # : 3601 Fairbanks Board of Agriculture, Division of Water Resources City, State, ZIP Code : Kansas City, KS 66106 Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL: 43.0 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 31.3 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 31.3 ft. below land surface measured on mo/day/yr 11/8/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 43.0 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 41.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 2 in. weight Flushmount well covers ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 24 ft. to 41 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 22 ft. to 41.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete from surface to 3.5 ft. Grout Intervals: From 3.5 ft. to 22 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?						
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS		
0	.4	Asphalt				
.4	1.0	Crushed Stone				
1.0	14.0	Light Brown Sandy Silt				
14.0	43.0	Light Brown Fine Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/8/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 510 This Water Well Record was completed on (mo/day/yr) 1-2-96 under the business name of MIKON Corporation by (signature) David Kram						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						